



LED DEC FG P45 4,5W/822 E14 DIM BX

Filament lamps are suitable for replacing clear incandescent bulbs and halogen lamps. The lamps emit plenty of light towards the base. This is very important for luminaires on which the base of the lamp points downward. The lamps emit warm yellow (2200 K) light and, when combined with the elegant cord, look impressive even without a lampshade. Models that are dimmable with LED dimmers can be recognised by the DIM symbol on the package. The eco-friendly cardboard packages are colour-coded. The colour indicates the corresponding incandescent bulb, making the choice simpler for the consumer. Technical specifications are also clearly presented.



Bulb type compact

PRODUCT CODE	GTIN1	L X H X W	KG	PRODUCT FAMILY
LED DEC FG P45 4,5W/822 E14 DIM BX				
9410729	6435200276179	45 x 80 x 45	0.020	DECOR

TECHNICAL DATAS (ETIM)			
Radiation angle (°)	360	Weighted energy consumption in 1,000 5 hours (kWh)	
Beam angle (°)	360		
ETIM class	EC001959	Length (mm)	80
Energy efficiency class	A++	Colour housing	Transparent
Photobiological safety according to EN 62471	RG1	Min. number of switching cycles	50000
Diameter (mm)	45	Power factor	0,7
Filament lamp	No	Colour of light	822
Dimmable	Yes	Colour of light acc. EN 12464-1	Warm <3300 K
Voltage type	AC	Light colour category	Warm
Socket	E14	Colour of light (max)	2200
With remote control	No	Colour of light (min)	2200
Remote operation possible	No	Lamp efficacy (lm/W)	89
Average nominal lifespan (h)	15000	Luminous flux (lm)	400
Degree of protection (IP)	Other	Luminous flux (max) (lm)	400
Lamp designation	Other	Luminous flux (min) (lm)	400
Lamp power (W)	4,5	Colour	Other
Lamp power (max) (W)	4,5	Colour controllable (RGB)	No
Lamp power (min) (W)	4,5	Colour temperature (K) (numeric)	2200
Lamp shape	Round/globe	Colour temperature (max) (K)	2200
Type of glass/cover	Clear	Colour temperature (min) (K)	2200
Nominal voltage (max) (V)	240	Colour rendering index CRI	80-89
Nominal voltage (min) (V)	220	Colour consistency (McAdam ellipse)	SDCM5