

## LED DEC FG A60 8,5W/830 E27 DIM BX

The unique feature of this series is the lamps' fully comprehensive 360-degree light distribution. The lamp also emits light in the direction of the base, which is particularly useful for ceiling luminaires, for example. An opal cover makes the light glareless. Models that are dimmable with LED dimmers can be recognised by the DIM symbol on the package. The lamps have a pleasant pure white tone (3000 K). Their ecofriendly cardboard packages are colour-coded. The colour indicates the corresponding incandescent bulb, making the choice simpler for the consumer. Technical specifications are also clearly presented.



Bulb type classic



PRODUCT CODE	GTIN1	LXHXW	KG	PRODUCT FAMILY
LED DEC FG A60 8,5W/	830 E27 DIM BX			
9410728	6435200276162	60 x 104 x 60	0.040	DECOR

adiation angle (°)	360	Nominal voltage (min) (V)	220
eam angle (°)	360	Weighted energy consumption in 1,000	9
TIM class	EC001959	hours (kWh)	
Energy Efficiency Index (EEI)	0,106	Length (mm)	104
Energy efficiency class	A++	Colour housing	White
Photobiological safety according to EN	RG1	Min. number of switching cycles	50000
62471		Power factor	0,7
Diameter (mm)	60	Colour of light	830
Filament lamp	No	Colour of light acc. EN 12464-1	Warm <3300 K
Dimmable	Yes	Light colour category	Warm
Voltage type	AC	Colour of light (max)	3000
Socket	E27	Colour of light (min)	3000
With remote control	No	Lamp efficacy (lm/W)	124
Remote operation possible	No	Luminous flux (lm)	1055
Average nominal lifespan (h)	15000	Luminous flux (max) (lm)	1055
Degree of protection (IP)	Other	Luminous flux (min) (lm)	1055
Lamp designation	A-type	Colour	White
Lamp power (W)	8,5	Colour controllable (RGB)	No
Lamp power (max) (W)	8,5	Colour temperature (K) (numeric)	3000
Lamp power (min) (W)	8,5	Colour temperature (max) (K)	3000
Lamp shape	Round/globe	Colour temperature (min) (K)	3000
Type of glass/cover	Opal	Colour rendering index CRI	80-89
Nominal voltage (max) (V)	240	Colour consistency (McAdam ellipse)	SDCM5

