

LED DEC FG P45 4,5W/830 E27 DIM BX

The unique feature of this series is the lamps' fully comprehensive 360-degree light distribution. The lamp also emits light in the direction of the base, which is particularly useful for ceiling luminaires, for example. An opal cover makes the light glareless. Models that are dimmable with LED dimmers can be recognised by the DIM symbol on the package. The lamps have a pleasant pure white tone (3000 K). Their ecofriendly cardboard packages are colour-coded. The colour indicates the corresponding incandescent bulb, making the choice simpler for the consumer. Technical specifications are also clearly presented.



Bulb type compact



| PRODUCT CODE | GTIN1 | LXHXW | KG | PRODUCT FAMILY | |
|------------------------------------|---------------|--------------|-------|----------------|--|
| LED DEC FG P45 4,5W/830 E27 DIM BX | | | | | |
| 9410726 | 6435200276148 | 45 x 78 x 45 | 0.020 | DECOR | |

| adiation angle (°) | 360 | Nominal voltage (min) (V) | 220 |
|--|-------------|--------------------------------------|--------------|
| eam angle (°) | 360 | Weighted energy consumption in 1,000 | 5 |
| TIM class | EC001959 | hours (kWh) | |
| Energy Efficiency Index (EEI) | 0,107 | Length (mm) | 78 |
| Energy efficiency class | A++ | Colour housing | White |
| Photobiological safety according to EN | RG1 | Min. number of switching cycles | 50000 |
| 52471 | | Power factor | 0,7 |
| Diameter (mm) | 45 | Colour of light | 830 |
| Filament lamp | No | Colour of light acc. EN 12464-1 | Warm <3300 K |
| Dimmable | Yes | Light colour category | Warm |
| Voltage type | AC | Colour of light (max) | 3000 |
| Socket | E27 | Colour of light (min) | 3000 |
| With remote control | No | Lamp efficacy (lm/W) | 104 |
| Remote operation possible | No | Luminous flux (lm) | 470 |
| Average nominal lifespan (h) | 15000 | Luminous flux (max) (lm) | 470 |
| Degree of protection (IP) | Other | Luminous flux (min) (lm) | 470 |
| Lamp designation | Other | Colour | White |
| Lamp power (W) | 4,5 | Colour controllable (RGB) | No |
| Lamp power (max) (W) | 4,5 | Colour temperature (K) (numeric) | 3000 |
| Lamp power (min) (W) | 4,5 | Colour temperature (max) (K) | 3000 |
| Lamp shape | Round/globe | Colour temperature (min) (K) | 3000 |
| Type of glass/cover | Opal | Colour rendering index CRI | 80-89 |
| Nominal voltage (max) (V) | 240 | Colour consistency (McAdam ellipse) | SDCM5 |
| | | | |

