



Oversikt

Leveringstid	Usually in Stock
--------------	------------------

General

Tilgjengelig utstyr	Installation guide Toolless mounting kit Brukermanual Vertical mounting brackets
---------------------	---

Physical

Kabellengde	3,00 m
Farge	Sort
Dybde	4,44 cm
Høyde	117,5 cm
Vekt	3,72 kg
Bredde	6,2 cm

Input

Permissible voltage	220...240 V
Max line current	32 A
Input current limits	32 A
Load capacity	7360 VA
Network frequency	50/60 Hz
Plug standard	IEC 60309 32 A 2P + E
Forsyningsspenning	200 V 208 V 230 V

Output

Number of power socket outlets	20 IEC 60320 C13 4 IEC 60320 C19
--------------------------------	-------------------------------------

Conformance

Produktsertifikater	CE TÜV EAC RCM
---------------------	-------------------------

Environmental

Omgivelsestemperatur drift	-5...45 °C
Relativ fuktighet	5...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0,00...15240,00 m

Forpakkingsinformasjon

Forpakning 1 vekt	4,48 kg
Forpakning 1 høyde	132 cm
Forpakning 1 bredde	16 cm
Forpakning 1 lengde	11 cm

Garantiperiode

Garanti	1 year repair or replace
---------	--------------------------