



Oversikt

Leveringstid	Usually in Stock
--------------	------------------

General

Tilgjengelig utstyr	Installation guide Brukermanual Vertical mounting brackets
---------------------	--

Physical

Kabellengde	3,00 m
Farge	Sort
Dybde	4,44 cm
Høyde	90,2 cm
Vekt	2,5 kg
Bredde	6,2 cm

Input

Input current limits	16 A
Load capacity	3680 VA
Network frequency	50/60 Hz
Plug standard	IEC 60309 16 A 2P + E
Forsyningsspenning	200 V 208 V 230 V

Output

Number of power socket outlets	18 IEC 60320 C13 3 IEC 60320 C19
--------------------------------	-------------------------------------

Conformance

Produktsertifikater	CE TÜV
---------------------	-----------

Environmental

Omgivelsestemperatur drift	-5...45 °C
Relativ fuktighet	5...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0,00...15240,00 m

Forpakkingsinformasjon

Forpakning 1 vekt	3 kg
Forpakning 1 høyde	132 cm
Forpakning 1 bredde	16 cm
Forpakning 1 lengde	11 cm

Garantiperiode

Garanti	1 year repair or replace
---------	--------------------------