



Oversikt

Leveringstid	Usually in Stock
--------------	------------------

Physical

Kabellengde	1,98 m
Farge	Sort
Dybde	4,44 cm
Høyde	150,6 cm
Vekt	3,08 kg
Bredde	6,2 cm

Input

Input current limits	16 A
Load capacity	11000 VA
Network frequency	50/60 Hz
Plug standard	IEC 60309 16 A 3P + N + PE
Forsyningsspenning	3 faser

Output

Number of power socket outlets	36 IEC 60320 C13 6 IEC 60320 C19
--------------------------------	-------------------------------------

Conformance

Produktsertifikater	CE TÜV EAC RCM
---------------------	-------------------------

Environmental

Omgivelsestemperatur drift	-5...45 °C
Relativ fuktighet	5...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0,00...15240,00 m

Forpakkingsinformasjon

Forpakning 1 vekt	4,28 kg
Forpakning 1 høyde	166 cm
Forpakning 1 bredde	16 cm
Forpakning 1 lengde	11 cm

Garantiperiode

Garanti	1 year repair or replace
---------	--------------------------