



Teknisk informasjon

Serie	PrismaSeT
Produktspekter	PrismaSeT P
Produkt eller type komponent	Front plate
Kompatibel med	PrismaSeT P cubicle
Tilbehør / separat del kategori	Installasjonstilbehør
Type frontplate	Utskjæring
Installert utstyr	ComPact: fixed NSX400 without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX400 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX400 without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX400 without earth leakage protection - control: motor mechanism - vertical installation ComPact: plug-in NSX400 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX400 without earth leakage protection - control: motor mechanism - vertical installation ComPact: drawout NSX400 without earth leakage protection - control: toggle - vertical installation ComPact: drawout NSX400 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: drawout NSX400 without earth leakage protection - control: motor mechanism - vertical installation ComPact: fixed NSX630 without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX630 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX630 without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX630 without earth leakage protection - control: motor mechanism - vertical installation ComPact: plug-in NSX630 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX630 without earth leakage protection - control: motor mechanism - vertical installation ComPact: drawout NSX630 without earth leakage protection - control: toggle - vertical installation ComPact: drawout NSX630 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: drawout NSX630 without earth leakage protection - control: motor mechanism - vertical installation
Polene beskrivelse	2 x 3P: mounting plate support: NSX400 vertical installation 2 x 4P: mounting plate support: NSX400 vertical installation 2 x 3P: mounting plate support: NSX630 vertical installation 2 x 4P: mounting plate support: NSX630 vertical installation
Driftsposisjon	Vertikal

Komplementær

Skap/kapsling beskrivelse	Cubicle - width 650 mm depth 400 mm
Posisjon for tilkopling	Direkte/Bolt tilkobling Linergy FC
Antall vertikale moduler	7
Standarder	IEC 61439-2 IEC 61439-1
Produktsertifikater	ASTA
Antall pr. sett	Sett á 1
Høyde	350 mm
Bredde	500 mm
Vekt	1,22 kg
Materiale	Stål
Type overflate	Matt Textured
Overflatebeskyttelse	Elektroforese behandling og hot-polymerisert polyester epoxy pulver
Farge	Hvit (RAL 9003)

Miljø

IK beskyttelsesklasse	IK07 conforming to EN/IEC 62262
-----------------------	---------------------------------

Offer Sustainability

REACH-regelverk	REACH-erklæring
REACH fri for SVHC	Ja
EU RoHS-direktiv	Proaktivt i samsvar (Produktet inngår ikke i EUs RoHS direktivet) EU RoHS-erklæring
Fri for giftige tungmetaller	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Kinas RoHS-forskrift	Kinas RoHS-Erklæring