

LVS04033

LINERGY DP 3P D.BLK/COMPACT 250A 27HOLES



Teknisk informasjon

Serie	Linergy
Produktspekter	Linergy
Produkt eller type komponent	Distribusjon blokk
Produktnavn	Linergy DP
Kompatibel med	PrismaSeT G enclosure PrismaSeT P enclosure Prisma PH kapsling PrismaSeT Pack 250 enclosure
Tilbehør / separat del kategori	Strømfordelingstilbehør
IP-grad	IPxx B

Montering	Prisma montasjeplate DIN skinne
Installert utstyr	EasyPact: fixed CVS100...250 without earth leakage protection - control: toggle - horizontal installation EasyPact: fixed CVS100...250 without earth leakage protection - control: direct front rotary handle - horizontal installation EasyPact: fixed CVS100...250 with earth leakage protection - control: toggle - horizontal installation EasyPact: fixed CVS100...250 with earth leakage protection - control: direct front rotary handle - horizontal installation EasyPact: fixed CVS100...250 without earth leakage protection - control: toggle - vertical installation EasyPact: fixed CVS100...250 without earth leakage protection - control: direct front rotary handle - vertical installation EasyPact: fixed CVS100...250 with earth leakage protection - control: toggle - vertical installation EasyPact: fixed CVS100...250 with earth leakage protection - control: direct front rotary handle - vertical installation Compact: fast INS250 - kontroll: direkte frontmontert dreiehåndtak - horisontal installasjon Compact: fast INS250 - kontroll: direkte frontmontert dreiehåndtak - Vertikal installasjon Compact: fast INS250 - kontroll: sidemontert grep - Vertikal installasjon Compact: fast INV100 - kontroll: direkte frontmontert dreiehåndtak - horisontal installasjon Compact: fast INV100 - kontroll: direkte frontmontert dreiehåndtak - Vertikal installasjon Compact: fast INV160 - kontroll: direkte frontmontert dreiehåndtak - horisontal installasjon Compact: fast INV160 - kontroll: direkte frontmontert dreiehåndtak - Vertikal installasjon Compact: fast INV200 - kontroll: direkte frontmontert dreiehåndtak - horisontal installasjon Compact: fast INV200 - kontroll: direkte frontmontert dreiehåndtak - Vertikal installasjon Compact: fast INV250 - kontroll: direkte frontmontert dreiehåndtak - horisontal installasjon Compact: fast INV250 - kontroll: sidemontert grep - Vertikal installasjon Compact: fast INV250 - kontroll: direkte frontmontert dreiehåndtak - Vertikal installasjon Compact: fast NSX100...250 og amperemeter uten jordfeilbeskyttelse - kontroll: kipp - horisontal installasjon ComPact: fixed NSX100...250 without earth leakage protection - control: toggle - horizontal installation ComPact: fixed NSX100...250 with earth leakage protection - control: toggle - horizontal installation ComPact: fixed NSX100...250 without earth leakage protection - control: direct front rotary handle - horizontal installation ComPact: fixed NSX100...250 with earth leakage protection - control: direct front rotary handle - horizontal installation ComPact: fixed NSX100...250 without earth leakage protection - control: motor mechanism - horizontal installation ComPact: plug-in NSX100...250 without earth leakage protection - control: toggle - horizontal installation ComPact: fixed NSX100...250 without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX100...250 with earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX100...250 without earth leakage protection - control: direct front rotary handle - vertical installation ComPact: fixed NSX100...250 with earth leakage protection - control: direct front rotary handle - vertical installation
Antall poler	3P
[Ue] merkespenning	690 V AC
[Ui] isolasjonsspenning	750 V AC
[Uimp] Nominell impuls-spenning	8 kV
[Ie] nominell driftsstrøm	250 A på 40 °C
[Icw] kort-tids/kortslutnings merkestrøm	8,5 kA for 1 s
[Ipk] tillatt peakstrøm	30 kA
I ² t på	72250000 A ² .s

Tilkoblingsklemmer	Supply: lug120 mm ² Fordeling: fjærklemmer (fase) , 6 x 4...10 mm ² (fleksibel) Fordeling: fjærklemmer (fase) , 3 x 6...16 mm ² (fleksibel) Fordeling: fjærklemmer (fase) , 6 x 4...10 mm ² (stiv) Fordeling: fjærklemmer (fase) , 3 x 6...16 mm ² (stiv)
Høyde	140 mm
Bredde	105 mm
Dybde	64 mm
Vekt	0,74 kg
Farge	Antrasitt grå (RAL 7016)

Miljø

Forurensninggrad	3
Overspenningskategori	III
Glødetrådtype	960 °C i samsvar med IEC 60695-2-11
Standarder	IEC 60947-7-1 IEC 61439-1, inside enclosure IEC 61439-2, inside enclosure
Produktsertifikater	ASTA
Omgivelsestemperatur drift	-25...55 °C

Offer Sustainability

REACH-regelverk	 REACH-erklæring
REACH fri for SVHC	Ja
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Fri for giftige tungmetaller	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Kinas RoHS-forskrift	 Kinas RoHS-Erklæring
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.