



Teknisk informasjon

Serie	PrismaSeT
Produktspekter	PrismaSeT P
Produkt eller type komponent	Skinne
Tilbehør / separat del kategori	Installasjonstilbehør
Kompatibel med	PrismaSeT P
Type festeskinne	Modulær

Installert utstyr	Acti 9: fast C120 uten jordfeilbeskyttelse - kontroll: kipp TeSys: fixed GV2LE TeSys: fixed GV2ME TeSys: fixed GV2RTn Acti 9: fast iC120 uten jordfeilbeskyttelse - kontroll: kipp Vigilohm: IM20 Vigilohm: IM20H Compact: fast INS100 - kontroll: direkte frontmontert dreiehåndtak - Vertikal installasjon Compact: fast INS160 - kontroll: direkte frontmontert dreiehåndtak - Vertikal installasjon Compact: fast INS40 - kontroll: direkte frontmontert dreiehåndtak - Vertikal installasjon Compact: fast INS63 - kontroll: direkte frontmontert dreiehåndtak - Vertikal installasjon Acti 9: fixed modular device Multi 9: fixed modular device Multi 9: fast NG125 uten jordfeilbeskyttelse - kontroll: kipp Multi 9: fast NG125 NA - kontroll: kipp Vigirex: RH10 Vigirex: RH21 Vigirex: RH99 Acti 9: fast C120 med jordfeilbeskyttelse - kontroll: kipp Acti 9: fast iC120 med jordfeilbeskyttelse - kontroll: kipp Multi 9: fast NG125 med jordfeilbeskyttelse - kontroll: kipp Acti 9: fixed 1/2 or 1 module lamp - horizontal installation Compact: fast INS125 - kontroll: direkte frontmontert dreiehåndtak - Vertikal installasjon Acti 9: fixed modular device <= 40 A Multi 9: fixed modular device <= 40 A Vigilohm: IM10 Vigilohm: IM10H Vigilohm: IM9 Vigilohm: IM9-OL Acti 9: measurement device Multi 9: measurement device Vigirex: RH197M
Polene beskrivelse	1 x 3P: fixed C120 1 x 4P: fixed C120 9 x 3P: fixed GV2LE 9 x 3P: fixed GV2ME 9 x 3P: fixed GV2RTn 1 x 3P: fixed iC120 1 x 4P: fixed iC120 1 x 3P: fixed INS100 vertical installation 1 x 4P: fixed INS100 vertical installation 1 x 3P: fixed INS160 vertical installation 1 x 4P: fixed INS160 vertical installation 1 x 3P: fixed INS40 vertical installation 1 x 4P: fixed INS40 vertical installation 1 x 3P: fixed INS63 vertical installation 1 x 4P: fixed INS63 vertical installation 1 x 3P: fixed NG125 1 x 4P: fixed NG125 1 x 3P: fixed NG125 NA 1 x 4P: fixed NG125 NA 1 x 3P: fixed INS125 vertical installation 1 x 4P: fixed INS125 vertical installation

Komplementær

Skap/kapsling beskrivelse	Cubicle - width 650 mm depth 400 mm
Kabinett nominell høyde	2000 mm
Antallet vertikale moduler (50 mm)	2 module(s): 1/2 or 1 module lamp, direct in 650 mm Widecubicle 5 module(s): C120 without earth leakage protection , direct in 650 mm Widecubicle 3 module(s): GV2LE, direct in 650 mm Widecubicle 3 module(s): GV2ME, direct in 650 mm Widecubicle 3 module(s): GV2RTn, direct in 650 mm Widecubicle 5 module(s): iC120 without earth leakage protection , direct in 650 mm Widecubicle 4 module(s): IM10 in 650 mm Widecubicle 4 module(s): IM10H in 650 mm Widecubicle 4 module(s): IM20 in 650 mm Widecubicle 4 module(s): IM20H in 650 mm Widecubicle 3 module(s): IM9 in 650 mm Widecubicle 3 module(s): IM9-OL in 650 mm Widecubicle 4 module(s): INS100, direct in 650 mm Widecubicle 5 module(s): INS100, direct in 650 mm Widecubicle 4 module(s): INS125, direct in 650 mm Widecubicle 5 module(s): INS125, direct in 650 mm Widecubicle 4 module(s): INS160, direct in 650 mm Widecubicle 5 module(s): INS160, direct in 650 mm Widecubicle 4 module(s): INS40, direct in 650 mm Widecubicle 4 module(s): INS63, direct in 650 mm Widecubicle 3 module(s): measurement device in 650 mm Widecubicle 3 module(s): modular device <= 40 A, direct in 650 mm Widecubicle 8 module(s): modular device <= 40 A, direct in 650 mm Widecubicle 4 module(s): modular device, direct in 650 mm Widecubicle 5 module(s): NG125 without earth leakage protection , direct in 650 mm Widecubicle 5 module(s): NG125 NA, direct in 650 mm Widecubicle 3 module(s): RH10 in 650 mm Widecubicle 3 module(s): RH197M in 650 mm Widecubicle 3 module(s): RH21 in 650 mm Widecubicle 3 module(s): RH99 in 650 mm Widecubicle 5 module(s): C120 with earth leakage protection , direct in 650 mm Widecubicle 5 module(s): iC120 with earth leakage protection , direct in 650 mm Widecubicle 5 module(s): NG125 with earth leakage protection , direct in 650 mm Widecubicle
9 mm polbredde	48
Antall pr. sett	Sett á 1
Høyde	43 mm
Bredde	592 mm
Dybde	126 mm
Vekt	0,5 kg
Farge	Natural
Materiale	Metall

Miljø

Standarder	IEC 61439-2 IEC 61439-1
Produktsertifikater	ASTA

Offer Sustainability

REACH-regelverk	 REACH-erklæring
REACH fri for SVHC	Ja
EU RoHS-direktiv	Proaktivt i samsvar (Produktet inngår ikke i EUs RoHS direktivet)  EU RoHS-erklæring
Fri for giftige tungmetaller	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Kinas RoHS-forskrift	 Kinas RoHS-Erklæring