



Teknisk informasjon

Serie	PrismaSeT
Produktspekter	PrismaSeT P
Produkt eller type komponent	Skinne
Tilbehør / separat del kategori	Installasjonstilbehør
Kompatibel med	PrismaSeT P
Type festeskinne	Regulerbar Modulær
Installert utstyr	TeSys: fixed GV2L TeSys: fixed GV2P TeSys: fixed GV3 Compact: fast NG160 uten jordfeilbeskyttelse - kontroll: kipp Compact: fast NG160 NA uten jordfeilbeskyttelse - kontroll: kipp Compact: fast NG160 med jordfeilbeskyttelse - kontroll: kipp Altistart: ATS01N Altistart: ATS01N103/106FT TeSys: fixed D or K contactors <= 40 A - horizontal installation TeSys: fixed GV2 + D or K contactors <= 40 A - horizontal installation TeSys: fixed TeSys U - horizontal installation PowerLogic: PM5500 PowerLogic: iEM3000 PowerLogic: PM3000 PowerLogic: PM5563RD Compact: fast NSXm uten jordfeilbeskyttelse - kontroll: kipp - Vertikal installasjon Compact: fast NSXm med jordfeilbeskyttelse - kontroll: kipp - Vertikal installasjon
Polene beskrivelse	9 x 3P: fixed GV2L 9 x 3P: fixed GV2P 7 x 3P: fixed GV3 1 x 3P: fixed NG160 1 x 4P: fixed NG160 1 x 3P: fixed NG160 NA 1 x 4P: fixed NG160 NA 9 x 4P: fixed D or K contactors <= 40 A horizontal installation 9 x 3P: fixed GV2 + D or K contactors <= 40 A horizontal installation 9 x 3P: fixed TeSys U horizontal installation 1 x 3P or 4P: fixed NSXm vertical installation

Komplementær

Skap/kapsling beskrivelse	Cubicle - width 650 mm depth 400 mm
Kabinett nominell høyde	2000 mm
Antallet vertikale moduler (50 mm)	5 module(s): ATS01N in 650 mm Widecubicle 6 module(s): ATS01N in 650 mm Widecubicle 4 module(s): ATS01N103/106FT in 650 mm Widecubicle 3 module(s): D or K contactors <= 40 A, direct in 650 mm Widecubicle 5 module(s): GV2 + D or K contactors <= 40 A, direct in 650 mm Widecubicle 3 module(s): GV2L, direct in 650 mm Widecubicle 3 module(s): GV2P, direct in 650 mm Widecubicle 5 module(s): GV3, direct in 650 mm Widecubicle 4 module(s): iEM3000 in 650 mm Widecubicle 5 module(s): NG160 without earth leakage protection , direct in 650 mm Widecubicle 5 module(s): NG160 NA without earth leakage protection , direct in 650 mm Widecubicle 8 module(s): NSXm without earth leakage protection , direct in 650 mm Widecubicle 4 module(s): PM3000 in 650 mm Widecubicle 3 module(s): PM5500 in 650 mm Widecubicle 3 module(s): PM5563RD in 650 mm Widecubicle 5 module(s): TeSys U, direct in 650 mm Widecubicle 4 module(s): TeSys U, direct in 650 mm Widecubicle 5 module(s): NG160 with earth leakage protection , direct in 650 mm Widecubicle 8 module(s): NSXm with earth leakage protection , direct in 650 mm Widecubicle
9 mm polbredde	48
Antall pr. sett	Sett á 1
Høyde	30 mm
Bredde	563 mm
Dybde	325 mm
Vekt	0,86 kg
Farge	Natural
Materiale	Metall

Miljø

Standarder	IEC 61439-1 IEC 61439-2
Produktsertifikater	ASTA

Offer Sustainability

REACH-regelverk	 REACH-erklæring
REACH fri for SVHC	Ja
EU RoHS-direktiv	Proaktivt i samsvar (Produktet inngår ikke i EUs RoHS direktivet)  EU RoHS-erklæring
Fri for giftige tungmetaller	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Kinas RoHS-forskrift	 Kinas RoHS-Erklæring