



Teknisk informasjon

Serie	PrismaSeT
Produktspekter	PrismaSeT G PrismaSeT P
Produkt eller type komponent	Front plate
Kompatibel med	PrismaSeT G enclosure PrismaSeT P cubicle
Tilbehør / separat del kategori	Installasjonstilbehør
Type frontplate	Utskjæring
Installert utstyr	Easypact: fast CVS100...160 med jordfeilbeskyttelse - kontroll: direkte frontmontert dreiehåndtak - Vertikal installasjon Easypact: fast CVS250 med jordfeilbeskyttelse - kontroll: direkte frontmontert dreiehåndtak - Vertikal installasjon Compact: fast NSX100...160 med jordfeilbeskyttelse - kontroll: direkte frontmontert dreiehåndtak - Vertikal installasjon ComPact: plug-in NSX100...160 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX100...160 with earth leakage protection - control: motor mechanism - vertical installation ComPact: drawout NSX100...160 with earth leakage protection - control: toggle - vertical installation ComPact: drawout NSX100...160 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: drawout NSX100...160 with earth leakage protection - control: motor mechanism - vertical installation ComPact: fixed NSX100...160 with earth leakage protection - control: motor mechanism - vertical installation Compact: fast NSX250 med jordfeilbeskyttelse - kontroll: direkte frontmontert dreiehåndtak - Vertikal installasjon ComPact: plug-in NSX250 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: plug-in NSX250 with earth leakage protection - control: motor mechanism - vertical installation ComPact: drawout NSX250 with earth leakage protection - control: toggle - vertical installation ComPact: drawout NSX250 with earth leakage protection - control: direct front rotary handle - vertical installation ComPact: drawout NSX250 with earth leakage protection - control: motor mechanism - vertical installation ComPact: fixed NSX250 with earth leakage protection - control: motor mechanism - vertical installation

Polene beskrivelse	4 x 3P: mounting plate support: CVS100...160 vertical installation 3 x 4P: mounting plate support: CVS100...160 vertical installation 4 x 3P: mounting plate support: CVS250 vertical installation 3 x 4P: mounting plate support: CVS250 vertical installation 4 x 3P: mounting plate support: NSX100...160 vertical installation 3 x 4P: mounting plate support: NSX100...160 vertical installation 4 x 3P: mounting plate support: NSX250 vertical installation 3 x 4P: mounting plate support: NSX250 vertical installation 2 x 3P: mounting plate support: NSX100...160 vertical installation 2 x 4P: mounting plate support: NSX100...160 vertical installation 2 x 3P: mounting plate support: NSX250 vertical installation 2 x 4P: mounting plate support: NSX250 vertical installation
Driftsposisjon	Vertikal

Komplementær

Skap/kapsling beskrivelse	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Cubicle - width 650 mm depth 400 mm
Posisjon for tilkopling	Direkte/Bolt tilkobling Linergy FC
Antall vertikale moduler	7
Standarder	IEC 61439-1 IEC 61439-2
Produktsertifikater	ASTA
Antall pr. sett	Sett á 1
Høyde	350 mm
Bredde	500 mm
Vekt	1,26 kg
Materiale	Stål
Type overflate	Matt Textured
Overflatebeskyttelse	Elektroforese behandling og hot-polymerisert polyester epoxy pulver
Farge	Hvit (RAL 9003)

Miljø

IK beskyttelsesklasse	IK07 conforming to EN/IEC 62262
-----------------------	---------------------------------

Offer Sustainability

REACH-regelverk	 REACH-erklæring
REACH fri for SVHC	Ja
EU RoHS-direktiv	Proaktivt i samsvar (Produktet inngår ikke i EUs RoHS direktivet)  EU RoHS-erklæring
Fri for giftige tungmetaller	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Kinas RoHS-forskrift	 Kinas RoHS-Erklæring