



Teknisk informasjon

Serie	Linery
Produktspekter	Linery
Produkt eller type komponent	Device feeder
Produktnavn	Linery FM
Kompatibel med	PrismaSeT G enclosure PrismaSeT P enclosure Prisma PH kapsling PrismaSeT Pack 160 enclosure PrismaSeT Pack 250 enclosure
Produktkompatibilitet	Spesialkapsling
IP-grad	IPxx B

Komplementær

Montering	DIN skinne Perforert bakplate Tett bakplate
Installert utstyr	Modulært utstyr
Antall poler	3P + N
[Ue] merkespenning	440 V AC
[Ui] isolasjonsspenning	500 V AC 50/60 Hz
[Uimp] Nominell impuls ­ spenning	6 kV
[Ie] nominell drifts ­ strøm	63 A
[In] merke ­ strøm	63 A at 40 °C
[Ip _k] tillatt peak ­ strøm	12 kA
I ² t på	2400000 A ² .s
Tilkoblings ­ klemmer	Supply: tunnel type terminal 25 mm ² Distribution: quick-connect terminal strips (phase) , 2 x 4...6 mm ² (rigid) Distribution: quick-connect terminal strips (phase) , 2 x 4...6 mm ² (flexible) Distribution: quick-connect terminal strips (neutral) , 4 x 4...6 mm ² (rigid) Distribution: quick-connect terminal strips (neutral) , 4 x 4...6 mm ² (flexible) Distribution: quick-connect terminal strips (phase) , 2 x 1.5...4 mm ² (rigid) Distribution: quick-connect terminal strips (phase) , 2 x 1.5...4 mm ² (flexible) Distribution: quick-connect terminal strips (neutral) , 4 x 1.5...4 mm ² (rigid) Distribution: quick-connect terminal strips (neutral) , 4 x 1.5...4 mm ² (flexible)
9 mm polbredde	24
Totalt antall 18 mm moduler	12
Vekt	0,46 kg
Farge	Antrasitt grå (RAL 7016)

Miljø

Standarder	IEC 61439-1, inside enclosure IEC 61439-2, inside enclosure IEC 60947-7-1
Produktsertifikater	ASTA

Offer Sustainability

REACH-regelverk	 REACH-erklæring
REACH fri for SVHC	Ja
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Fri for giftige tungmetaller	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Kinas RoHS-forskrift	 Kinas RoHS-Erklæring
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.