

C123160BS

switch disconnecter ComPacT NSXm NA, 3P,
160 A rating, compression lugs and busbar
connectors



Teknisk informasjon

Serie	ComPacT new generation
Produktnavn	ComPacT NSXm new generation
Produkt eller type komponent	Lastbryter
Antall poler	3P
Type nettverk	AC
[Ue] merkespenning	690 V AC 50/60 Hz conforming to IEC 60947-2
[Ie] nominell driftsstrøm	AC-23: 100 A AC 50/60 Hz AC-22: 160 A AC 50/60 Hz
[Ui] isolasjonsspenning	800 V conforming to IEC 60947-2
[Uimp] Nominell impuls-spenning	8 kV conforming to IEC 60947-2
[Icm] maks nominell slutteevne ved kortslutning	2,13 kA
Kode for bryteevne	NA
Egnethet for isolasjon	Yes conforming to EN/IEC 60947-3
Kontaktposisjonsindikering	Ja
Driftskategori	Kategori A

Komplementær

Kontrolltype	Kipp
Monteringsmetode	Klips på Med skruer
Montering	35 mm symmetrical DIN rail Plate
[Icw] kort-tids/kortslutnings merkestrøm	1,5 kA under 3 s i samsvar med IEC 60947-3
Mekanisk levetid	20000 cycles In conforming to IEC 60947-3
Elektrisk levetid	AC-22A: 20000 cycles 440 V AC 50/60 Hz Ie/2 conforming to IEC 60947-3 AC-23A: 20000 cycles 440 V AC 50/60 Hz Ie/2 conforming to IEC 60947-3 AC-22A: 10000 cycles 440 V AC 50/60 Hz Ie conforming to IEC 60947-3 AC-23A: 10000 cycles 440 V AC 50/60 Hz Ie conforming to IEC 60947-3 AC-22A: 10000 cycles 690 V AC 50/60 Hz Ie/2 conforming to IEC 60947-3 AC-23A: 6000 cycles 690 V AC 50/60 Hz Ie/2 conforming to IEC 60947-3 AC-22A: 5000 cycles 690 V AC 50/60 Hz Ie conforming to IEC 60947-3 AC-23A: 3000 cycles 690 V AC 50/60 Hz Ie conforming to IEC 60947-3
Høyde	137 mm
Bredde	81 mm
Dybde	80 mm
Vekt	1,06 kg
Tilkoblingsklemmer	Compression lug/busbar

Miljø

Standarder	EN/IEC 60947
Produktsertifikater	EAC CCC
IP-grad	IP40 conforming to IEC 60529
IK beskyttelsesklasse	IK07 conforming to IEC 62262
Forurensningsgrad	3 i samsvar med IEC 60664-1
Omgivelsestemperatur drift	-25...70 °C
Omgivelsestemperatur for lagring	-50...85 °C

EU RoHS-direktiv	Analyseres
------------------	------------