

Wall mounted receptacle
Part no. 27004VN




- screw terminals
- external fixing
- cable entry at top
- nickel-plated contacts

Technical specifications

Ampere	16 A
Poles	5 p
Voltage	400 V
Clock position	6 h
Hertz	50-60 Hz
Connection technology	Screw terminals
Contact	nickel plated contacts, highly heat resistant contact carrier
Protection type	IP 44
Weight	270 g

Drawing



Zeichnung	Amp.	16			32		
1 MB 463	Pole	3	4	5	3	4	5
Maße in mm	a	95	93	92,5	102	102	102
	b	73,5	87,5	87,5	94	94	94
	c	93	107,5	110	115,5	115,5	119,5
	d	55,5	55,5	55,5	62	62	62
	e	61	76	76	84	84	84
	f1	5,3	5,3	5,3	5,1	5,1	5,1
	f2	5,3	5,3	5,3	5,1	5,1	5,1
	h	139	139	136,5	160	160	156,5
	i	19,8	21,5	21,5	26,5	26,5	26,5
	M	20x	25x	25x	25x	32x	32x
Klemmen für Leiterquer-		1,5	1,5	1,5	1,5	1,5	1,5
schnitt von bis mm²		1,5	1,5	1,5	2,5	2,5	2,5
		—4	—4	—4	—6	—6	—6