

Panel mounted receptacle  
Part no. 1485




- screw terminals
- 20° inclination
- 32 A receptacles optional fitted with auxiliary contact

Technical specifications

|                           |                     |
|---------------------------|---------------------|
| Ampere                    | 16 A                |
| Poles                     | 5 p                 |
| Voltage                   | 400 V               |
| Clock position            | 6 h                 |
| Hertz                     | 50-60 Hz            |
| Connection technology     | Screw terminals     |
| Contact                   | standard            |
| Protection type           | IP 67               |
| Flange                    | 100x92 mm           |
| Fixing hole               | 85x77 mm            |
| Inclination               | 20 °                |
| Weight                    | 237 g               |
| Declaration of Conformity | VDE, EAC, Kema, CQC |

Drawing



|                                                  |       |      |     |     |     |     |     |
|--------------------------------------------------|-------|------|-----|-----|-----|-----|-----|
| Drawing<br>1 MB 251                              | Amp.  | 16   |     |     | 32  |     |     |
|                                                  | Poles | 3    | 4   | 5   | 3   | 4   | 5   |
| Dim. in mm                                       | a     | 73.5 | 100 | 100 | 100 | 100 | 100 |
|                                                  | b     | 64   | 92  | 92  | 92  | 92  | 92  |
|                                                  | c     | 52   | 60  | 62  | 64  | 64  | 66  |
|                                                  | d     | 60   | 85  | 85  | 85  | 85  | 85  |
|                                                  | e     | 52   | 77  | 77  | 77  | 77  | 77  |
|                                                  | f     | 5.5  | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 |
|                                                  | g     | 8    | 8   | 8   | 8   | 8   | 8   |
|                                                  | g.1   | 2    | 2   | 2   | 2   | 2   | 2   |
|                                                  | h     | 84   | 100 | 105 | 109 | 109 | 113 |
|                                                  | i     | 78   | 85  | 96  | 103 | 103 | 110 |
|                                                  | k     | 49   | 32  | 32  | 53  | 53  | 45  |
|                                                  | l     | 52   | 55  | 65  | 67  | 67  | 72  |
|                                                  | l1    | 60   | 63  | 72  | 82  | 82  | 85  |
|                                                  | α     | 20°  | 20° | 20° | 20° | 20° | 20° |
| Terminal for cond. cross section (mm²) min.-max. |       | 1.5  | 1.5 | 1.5 | 2.5 | 2.5 | 2.5 |
|                                                  |       | —4   | —4  | —4  | —10 | —10 | —10 |