

**AMAXX® receptacle combination**  
Part no. 936074




- pre-wired for installation
- enclosure and insert made of AMAPLAST
- fusing behind a transparent cover

Technical specifications

|                           |                                                                                                                                                                           |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CEE 16 A, 4 p, 230 V      | 1                                                                                                                                                                         |
| SCHUKO® 16 A, 230 V       | 2                                                                                                                                                                         |
| Fusing                    | <ul style="list-style-type: none"><li>• 2 RCBOs 16A, 2p, 0,03 A</li><li>• 1 MCB 16A, 3p</li><li>• 1 RCD 40A, 4p, 0,03 A</li><li>• 1 Switch-Disconnecter 63A, 4p</li></ul> |
| Connection / feeder cable | <ul style="list-style-type: none"><li>• for 1 cable up to 4 * 16 mm²</li></ul>                                                                                            |
| Protection type           | IP 44                                                                                                                                                                     |
| Shutter                   | false                                                                                                                                                                     |
| Enclosure material        | Plastic                                                                                                                                                                   |

Drawing



Drawing 1 MB 522

Depth dimensions at various fittings.

| Receptacles       | Degrees | Depth  |
|-------------------|---------|--------|
| SCHUKO®16A, 230 V | IP 44   | 175 mm |
|                   | IP 67   | 194 mm |
| CEE 16A, 3p, 230V | IP 44   | 204 mm |
|                   | IP 67   | 205 mm |
| CEE 16A, 5p, 400V | IP 44   | 209 mm |
|                   | IP 67   | 213 mm |
| CEE 32A, 5p, 400V | IP 44   | 221 mm |
|                   | IP 67   | 227 mm |
| CEE 63A, 5p, 400V | IP 44   | 248 mm |
|                   | IP 67   | 248 mm |

Cable entries: closed for cut out. 2 x M 40 each on top and bottom, 2 x M 20 each on top and bottom for cut out.