

AMAXX® receptacle combination
Part no. 946309




- pre-wired for installation
- enclosure and insert made of AMAPLAST
- fusing behind a transparent cover

Technical specifications

CEE 32 A, 5 p, 400 V	1
CEE 16 A, 5 p, 400 V	1
SCHUKO® 16 A, 230 V	2
Fusing	• 2 RCBOs 16A, 2p, 0,03 A • 1 MCB 32A, 4p • 1 RCD 40A, 4p, 0,03 A • 1 MCB 16A, 4p • 1 RCD 40A, 4p, 0,03 A • 1 Switch-Disconnecter 63A, 4p
Connection / feeder cable	• for 1 cable up to 5* 25 mm²
Protection type	IP 44
Shutter	false
Enclosure material	Plastic
Weight	7550 g

Drawing



Drawing 1 MB 523

Depth dimensions at various fittings.

Receptacles	Degrees	Depth
SCHUKO® 16A, 230 V	IP 44	186 mm
	IP 67	208 mm
CEE 16A, 3p, 230V	IP 44	216 mm
	IP 67	220 mm
CEE 16A, 5p, 400V	IP 44	222 mm
	IP 67	226 mm
CEE 32A, 5p, 400V	IP 44	231 mm
	IP 67	236 mm
CEE 63A, 5p, 400V	IP 44	260 mm
	IP 67	260 mm

Cable entries: closed for cut out. 2 x M 40 each on top and bottom, 2 x M 20 each on top and bottom for cut out.