



Oversikt

Presentasjon	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Leveringstid	Usually in Stock

General

Inkludert utstyr	CD with software Rack mounting brackets Rack mounting support rails Smart UPS signalling RS-232 cable Brukermanual USB cable
Performance multiplier	1
Number of tare power	37 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
Size UPS version	Internetworking Server
UPS size	S
Value multiplier	1

Physical

Number of rack unit	1U
Farge	Sort
Dybde	66 cm
Høyde	4,4 cm
Montasjeplassering	Front
Mounting preference	Lower
Vekt	21,82 kg
Monteringsmetode	Rack-mounted
Two post mountable	0
USB compatible	Yes
Bredde	43,2 cm

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	IEC 320 C14
Input voltage limits	151...302 V adjustable 160...286 V
Antall kabler	1
Forsyningsspenning	230 V

Output

Merkeeffekt i W	640 W
Maximum configurable power in W	640 W
Harmonic distortion	Mindre enn 5 % ved full last
Output frequency	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	4 IEC 320 C13 2 IEC Jumpers
Curve equation	Efficiency
Curve load maximum	100 %
Curve X-axis maximum	100 %
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	1000 VA
Merkeeffekt VA	1000 VA

Conformance

Produktsertifikater	C-Tick CE GOST VDE
Standarder	EN 50091-1 EN 50091-2

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0,00...15240,00 m
Akkustikknivå	55 dBA
Varmeavgivelse	130 Btu/t
Show note OP temperature	No

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	2 t
Number of battery replacement quantity	1
Tilleggsinformasjon	Configurable for 220 : 230 or 240 nominal output voltage
Liquid value	0
Battery curve	Z
Battery charger power	107 W rated
Battery power in VAH	216 VAh runtime
Batterilevetid	4...6 år
Extended runtime	0

Communications & Management

Ledige plasser	1
Control panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rate	480 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Forpakning 1 vekt	25,45 kg
Forpakning 1 høyde	19,1 cm
Forpakning 1 bredde	55,9 cm
Forpakning 1 lengde	77,5 cm
Antall enheter forpakning 3	8

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	REACH-erklæring
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Miljøinformasjon	Produktmiljøprofil
Produktets livssyklus	Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt

Garantiperiode

Garanti	2 years repair or replace
---------	---------------------------