

SBP5000RMI2U

APC Service Bypass Panel- 230V; 32A; BBM;
IEC320 C20/HW input; IEC-320 Output- (2)
C19 (8) C13



Oversikt

Leveringstid	Usually in Stock
--------------	------------------

General

Tilgjengelig utstyr	Hardwire panel Installation guide Rack mounting brackets Brukermanual Wall mounting brackets
---------------------	---

Physical

Farge	Sort
Dybde	66 cm
Høyde	8,9 cm
Vekt	11,36 kg
Bredde	43,2 cm

Input

Network frequency	50/60 Hz
Number of input connectors	1 hard wire 3-wire (1P + N + E)
Plug standard	IEC 60320 C20
Antall kabler	1
Max line current	32 A
Input current limits	32 A
Load capacity	7680 VA
18 mm avstand	0...1
Forsyningsspenning	230 V

Output

Max current draw	32 A
Number of power socket outlets	8 IEC 60320 C13 2 IEC 60320 C19
Type vern	Strømbryter
Effektivitet	99 %
Output voltage	230 V

Conformance

Produktsertifikater	CSA GOST
Standarder	EN/IEC 62040-1 UL 1778

Environmental

Omgivelsestemperatur drift	-20...50 °C
Relativ fuktighet	0...95 %
Driftshøyde	0...15000 ft
Omgivelsestemperatur for lagring	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0,00...15240,00 m

Packing Units

Forpakning 1 vekt	23,18 kg
Forpakning 1 høyde	20,3 cm
Forpakning 1 bredde	61 cm
Forpakning 1 lengde	99,1 cm
Antall enheter forpakning 3	10

Offer Sustainability

EU RoHS-direktiv	Analyseres
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.

Garantiperiode

Garanti	2 years (parts only)
---------	----------------------