## nVent CADDY Cat HP J-Hook with Angle Bracket - CAT48HPAB (181212)







- Ideal for attaching to concrete, steel or wood surfaces
- Provides optimal support for high-performance data cable, up to and including Cat 5e, Cat 6, Cat 6A, Cat 7 and fibre optic
- · Provides superior fill capacity and load rating over most other non-continuous cable support alternatives
- Rounded edges on J-Hooks provide proper bend radius support for high performance data cables
- Cost effective alternative to expensive cable tray
- Complies with EN 50174-2
- Meets ISO®/IEC 14763-2, ANSI®/TIA 568 and ANSI®/TIA 569











|                             | DIN 4100-12 DIN 4102-12 DIN 4102-22  |
|-----------------------------|--|
| Part Number                 | CAT48HPAB  |
| Article Number              | 181212   |
| Material                    | Steel  |
| Finish                      | Pregalvanized  |
| Diameter (Ø)                | 75 mm  |
| Area                        | 5,974 mm²  |
| Cable Capacity, Cat 5e      | 200  |
| Cable Capacity, Cat 6       | 150  |
| Cable Capacity, Cat 6A      | 80   |
| Hole Size (HS)              | 6.3 mm   |
| Static Load (F)             | 270 N  |
| Certifications              | cULus<br>DIN 4102-12 abP P-3117/339/14-MPA BS (Germany)<br>E30<br>E60<br>E90 |
| Standard Packaging Quantity | 25 pc  |
| UPC                         | 78285671676  |
| EAN-13                      | 8711893125634  |

Non-continuous supports may not exceed spacing of 5' (1.5 m) per TIA 569-C.9.7 and EN 50174-2. Cable capacity is calculated based on a 70% fill rate.



ANSI is a registered trademark of American National Standards Institute. ISO is a registered trademark of International Organization for Standardization. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

nevent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent 's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2021 nVent All rights reserved nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

