




Oversikt

Presentasjon	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Leveringstid	Usually in Stock

General

Inkludert utstyr	CD with software Documentation CD Installation guide Rack mounting support rails Smart UPS signalling RS-232 cable USB cable
Performance multiplier	1
Number of tare power	27 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
Size UPS version	Internetworking Server Telecom
UPS size	S
Value multiplier	1

Physical

Number of rack unit	2U
Farge	Sort
Dybde	45,7 cm
Høyde	8,6 cm
Montasjeplassering	Front
Mounting preference	Lower
Vekt	28,64 kg
Monteringsmetode	Rack-mounted
Two post mountable	0
USB compatible	Yes
Bredde	43,2 cm

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	IEC 320 C14
Input voltage limits	151...302 V Justbar 160...286 V
Inputvolt_other	220 V 240 V
Forsyningsspenning	230 V

Output

Merkeeffekt i W	1000 W
Maximum configurable power in W	1000 W
Harmonic distortion	Mindre enn 5 % ved full last
Output frequency	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains
Outputvolt_other	220 V 240 V
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	4 IEC 320 C13 2 IEC Jumpers
Curve equation	Efficiency
Curve fixed loss	0,0102
Curve load maximum	100 %
Curve load minimum	2 %
Curve proportional loss	0
Curve square loss	0,0043
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 230V/50Hz electrical input and balanced resistive load (PF =
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	1500 VA
Merkeeffekt VA	1500 VA
Transfer time	2 ms typical

Conformance

Produktsertifikater	CE CSA EAC RCM TÜV VDE
Standarder	EN/IEC 62040-1 EN/IEC 62040-2

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-15...45 °C
Storage altitude	0,00...15240,00 m
Akkustikknivå	46 dBA
Varmeavgivelse	90 Btu/t
Show note OP temperature	No

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 t
Number of battery replacement quantity	1
Tilleggsinformasjon	Configurable for 220 : 230 or 240 nominal output voltage
Liquid value	0
Battery curve	Z
Battery charger power	144 W rated
Battery power in VAH	432 VAh runtime
Batterilevetid	4...6 år
Extended runtime	0

Communications & Management

Ledige plasser	1
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency power off	Optional

Surge Protection and Filtering

Surge energy rate	459 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Forpakning 1 vekt	31,91 kg
Forpakning 1 høyde	25,1 cm
Forpakning 1 bredde	59,4 cm
Forpakning 1 lengde	60,3 cm
Antall enheter forpakning 3	8

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt

WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt

Garantiperiode

Garanti	3 years repair or replace (excluding battery) and 2 years for battery
---------	---