

AP8704R-WW

Power Cord Kit (6 ea), Locking, C13 to C14 (90 Degree), 1.2m



Oversikt

Presentasjon	Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.
Leveringstid	Usually in Stock

General

Tilgjengelig utstyr	3 left-angle jumper cords 3 right-angle jumper cords
---------------------	---

Physical

Kabellengde	1,22 m
Farge	Sort
Dybde	4,5 cm
Høyde	24 cm
Vekt	1,01 kg
Bredde	7 cm

Input

Plug standard	IEC 60320 C14
Antall kabler	6
Max line current	10 A
Input current limits	10 A

Output

Max current draw	10 A
Number of power socket outlets	1 IEC 60320 C13
Power cable length	1,22 m

Conformance

Produktsertifikater	CCC PSE VDE
---------------------	-------------------

Environmental

Omgivelsestemperatur drift	0...70 °C
Relativ fuktighet	20...80 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-25...75 °C
Storage Relative Humidity	20...80 %
Storage altitude	0,00...15240,00 m

Packing Units

Forpakning 1 vekt	1,01 kg
Forpakning 1 høyde	24 cm
Forpakning 1 bredde	7 cm
Forpakning 1 lengde	4,5 cm
Antall enheter forpakning 3	390

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Blyfri	Ja
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.

Garantiperiode

Garanti	2 years repair or replace
---------	---------------------------