



Oversikt

Presentasjon



APC Metered Rack Power Distribution Units (PDUs) provide active metering to enable energy optimization and circuit protection. User-defined alarm thresholds mitigate risk with real-time local and remote alerts to warn of potential circuit overloads. Metered Rack PDUs provide power utilization data to allow Data Center Managers to make informed decisions on load balancing and right sizing IT environments to lower total cost of ownership. Metered Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and ultra low profile circuit breakers. Users can access and configure Metered Rack PDUs through secure Web, SNMP, or Telnet Interfaces which are complimented by APC Centralized Management platforms using InfraStruxure Central, Operations, Capacity, and Energy Efficiency.

Leveringstid

Usually in Stock

General

Tilgjengelig utstyr

Installation guide
Locking input power cord
Rack mounting brackets
Serial configuration cable
Safety guide

Physical

Kabellengde	3,00 m
Farge	Sort
Dybde	4,4 cm
Høyde	90,2 cm
Vekt	2,93 kg
Bredde	5,6 cm

Input

Permissible voltage	100...240 V
Max line current	16 A
Input current limits	16 A
Load capacity	3700 VA
Network frequency	50/60 Hz
Plug standard	IEC 60309 16 A 2P + E
Forsyningsspenning	200 V 208 V 230 V

Output

Number of power socket outlets	18 IEC 60320 C13 2 IEC 60320 C19
--------------------------------	-------------------------------------

Conformance

Produktsertifikater	METI Denan VDE
Standarder	CSA C22.2 No 60950 IEC 60950 UL 60950-1

Environmental

Omgivelsestemperatur drift	-5...45 °C
Relativ fuktighet	5...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0,00...15240,00 m

Packing Units

Forpakning 1 vekt	4,92 kg
Forpakning 1 høyde	112,4 cm
Forpakning 1 bredde	16,2 cm
Forpakning 1 lengde	10,7 cm

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Blyfri	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt

Garantiperiode

Garanti	2 years repair or replace
---------	---------------------------