



Teknisk informasjon

Range of product	Actassi
Produkt eller type komponent	Fiberpanel 19" bestykket
Farge	Panel: black (RAL 9005) MTP adapter: black LCq adapter: magenta
Antall pr. sett	1

Komplementær

Fiber ytelse	OM4
Maximum insertion loss	MTP: <0.5 dB at 850 nm LC: <0.3 dB at 850 nm
Minimum return loss	20 DB 850 nm MTP 20 dB 850 nm LC
Number of rack unit	1U
Terminering 1	24 x LC quad
Terminering 2	8 x 12 MTP
Brukervilkår	Innendørs
Overflatebehandling	Panel: epoxy
Materiale	Sheet steel panel PEI (polyetherimide) MTP adapter PBT (polybutylene terephthalate) LCq adapter
Montering av enhet	Innfelt
Festemetode	Mutter
Høyde	44 mm
Bredde	483 mm
Dybde	270 mm
Gjeldende land	Europe

Miljø

Omgivelsestemperatur for drift	-10...60 °C
Omgivelsestemperatur for lagring	-25...70 °C
Standarder	IEC 61754-20 LC adapter IEC 50377-7-x LC adapter IEC 61754-7 MTP adapter EN 50377-15-1 MTP adapter TIA/EIA-604-5 MTP adapter ISO/IEC 11801:2011 Ed.2.2 ISO/IEC 24764 ISO/IEC 14763-3 TIA/EIA-568-C.3 ANSI/TIA-942 IEEE 802.3ae 10Gbase-SR

Packing Units

Enhetstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	2,1 kg
Forpakning 1 høyde	5,7 cm
Forpakning 1 bredde	31 cm
Forpakning 1 lengde	51 cm

Garantiperiode

Garanti	18 måneder
---------	------------