



Oversikt

Leveringstid	Usually in Stock
--------------	------------------



General

Tilgjengelig utstyr	Installation guide
---------------------	--------------------

Physical

Kabellengde	2,44 m
Farge	Sort
Dybde	25,4 cm
Høyde	4,4 cm
Vekt	4,84 kg
Bredde	43,7 cm

Input

Permissible voltage	200...250 V
Max line current	32 A
Input current limits	32 A
Load capacity	22000 VA
Network frequency	47...63 Hz
Plug standard	IEC 60309 32 A 3P + N + PE
Forsyningsspenning	400 V 3 phases

Output

Number of power socket outlets	6 IEC 60320 C19
--------------------------------	-----------------

Conformance

Produktsertifikater	CE GOST VDE
---------------------	-------------------

Environmental

Omgivelsestemperatur drift	-5...45 °C
Relativ fuktighet	5...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0,00...15240,00 m

Packing Units

Forpakning 1 vekt	6,98 kg
Forpakning 1 høyde	24,1 cm
Forpakning 1 bredde	55,9 cm
Forpakning 1 lengde	50,2 cm

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	REACH-erklæring
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Blyfri	Ja
Optimalisert energieffektivitet	Energieffektivt produkt

Garantiperiode

Garanti	2 years repair or replace
---------	---------------------------