

BH500INET

APC Back-UPS 500 Structured Wiring UPS, 230V



Oversikt

Leveringstid	Usually in Stock
--------------	------------------

General

Inkludert utstyr	CD with software User manual Cat 6 Ethernet cable Installation guide
Performance multiplier	1
Number of tare power	7 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
Size UPS version	Internetworking Telecom Workstation
UPS size	WS
Value multiplier	1

Physical

Kabellengde	2,44 m
Farge	Beige
Dybde	10,5 cm
Høyde	37,2 cm
Montasjeplassering	Front
Mounting preference	No preference
Vekt	7,42 kg
Monteringsmetode	Not rack-mountable
Two post mountable	0
USB compatible	No
Bredde	22,5 cm

Input

Network frequency	47...63 Hz
Plug standard	IEC 60320 C14
Maximum input current	4 A
Brytekapasitet, A	4 A
Antall kabler	1
Forsyningsspenning	230 V

Output

Merkeeffekt i W	300 W
Maximum configurable power in W	300 W
Output frequency	47...63 Hz sync to mains
UPS type	Standby
Wave type	Stepped approximation to a sinewave
Nb of power socket outlets	4 IEC 60320 C13 2 IEC Jumpers
Curve equation	Efficiency
Curve fixed loss	0,0121
Curve load maximum	100 %
Curve load minimum	2 %
Curve proportional loss	0
Curve square loss	0,0003
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 230V/50Hz electrical input and balanced resistive load (PF =
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	500 VA
Merkeeffekt VA	500 VA

Conformance

Produktsertifikater	A-Tick C-Tick GOST NEMKO
Equipment protection policy	Lifetime : 10000 euros

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	5...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0,00...15240,00 m
Akkustikknivå	40 dBA
Show note OP temperature	No

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 t
Number of battery replacement quantity	1
Liquid value	0
Batterispenningen	12 V
Kapasitet på batteri	7,0 Ah
Battery curve	B
Battery charger power	10 W rated
Battery power in VAH	77 VAh runtime
Batterilevetid	4...6 år
Extended runtime	0

Communications & Management

Control panel	LED status display with on line : on battery : replace battery and building wiring fault Network link status LED
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	600 J
Data line protection	RJ11 analog phone line for phone/fax/modem/DSL RJ45 network line - 10/100 base-T Ethernet Coaxial cable for CATV/SATV/modem/audio-video

Packing Units

Forpakning 1 vekt	8,41 kg
Forpakning 1 høyde	47 cm
Forpakning 1 bredde	30,5 cm
Forpakning 1 lengde	16,5 cm
SCC14	10731304206412
Antall enheter forpakning 2	1
Forpakning 2 vekt	16,81 kg
Forpakning 2 lengde	476,25 mm
Antall enheter forpakning 3	48

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt

Garantiperiode

Garanti	2 year (manufacturer's defect)
---------	--------------------------------