



Oversikt

Leveringstid	Usually in Stock
--------------	------------------

General

Inkludert utstyr	CD with software Telephone cable User manual USB cable Warranty card
Performance multiplier	1
Number of tare power	30 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS
Value multiplier	1

Physical

Kabellengde	1,52 m
Dybde	38,2 cm
Høyde	30,1 cm
Mounting preference	No preference
Vekt	13 kg
Monteringsmetode	Not rack-mountable
Two post mountable	0
USB compatible	No
Bredde	11,2 cm

Input

Network frequency	50 Hz +/- 1 Hz 60 Hz +/- 1 Hz
Plug standard	Schuko CEE 7/7P
Input voltage limits	156...300 V Justrbar 176...294 V
Maximum input current	10 A
Brytekapasitet, A	10 A
Forsyningsspenning	230 V

Output

Merkeeffekt i W	720 W
Maximum configurable power in W	720 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Nb of power socket outlets	3 Schuko CEE 7 3 Schuko CEE 7 surge
Bypass type	Built-in bypass
Curve equation	Efficiency
Curve fixed loss	0,0104
Curve load maximum	100 %
Curve load minimum	2 %
Curve proportional loss	0
Curve square loss	0,0022
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 230V/50Hz electrical input and balanced resistive load (PF =
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	1200 VA
Merkeeffekt VA	1200 VA
Transfer time	10 ms typical : 12 ms maximum

Conformance

Produktsertifikater	BSI 1363 CE NEMKO
Equipment protection policy	Lifetime : 200000 AUD Lifetime : 150000 euros Lifetime : 75000 GBP

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0,00...15240,00 m
Akkustikknivå	45 dBA
Show note OP temperature	No

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 t
Liquid value	0
Batterispenningen	24 V
Kapasitet på batteri	9,0 Ah
Battery curve	C
Battery charger power	23 W rated
Battery power in VAh	187 VAh runtime
Extended runtime	0

Surge Protection and Filtering

Surge energy rate	441 J
Data line protection	RJ11 modem/fax/DSL protection (two wire single line) RJ45 modem/fax/DSL protection (four wire dual line)

Packing Units

Forpakning 1 vekt	13,8 kg
Forpakning 1 høyde	39 cm
Forpakning 1 bredde	23,5 cm
Forpakning 1 lengde	49 cm
SCC14	10731304286834

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt

Garantiperiode

Garanti	2 years repair or replace, 3 years repair or replace for European Union countries
---------	---