

VDILC265D1D

Actassi preterminert fiber kassett 2x12
MTP-24x1 LC OS2



Teknisk informasjon

Produkt eller type komponent	Fiberkassett bestykket
Farge	Cassette: black (RAL 9005) LC adapter: blue MTP adapter: green
Overflatebehandling	Cassette: epoxy
Antall pr. sett	1

Komplementær

Produsert i	Rammeprofil Fiberpanel ubestyyket
Terminering 1	12 x LC duplex
Terminering 2	2 x 12 MTP
Minimum return loss	50 DB 1310 nm MTP 50 DB 1550 nm MTP 45 DB 1310 nm LC 45 dB 1550 nm LC
Maximum insertion loss	MTP: <0.5 dB at 1310 nm MTP: <0.5 dB at 1550 nm LC: <0.3 dB at 1310 nm LC: <0.3 dB at 1550 nm
Number of rack unit	1U
Fiber ytelse	OS2
Materiale	Aluminium alloy: cassette PBT (polybutylene terephthalate): LC adapter PEI (polyetherimide): MTP adapter
Installasjonstype	Innendørs
Montering av enhet	Innfelt
Mounting type	By captive screws
Høyde	37 mm
Bredde	105 mm
Dybde	124,5 mm
Gjeldende land	Europe

Miljø

Omgivelsestemperatur for lagring	-25...70 °C
Omgivelsestemperatur drift	-10...60 °C
Standarder	LC adapter: IEC 61754-20 LC adapter: IEC 50377-7-x MTP adapter: IEC 61754-7 MTP adapter: EN 50377-15-1 MTP adapter: TIA/EIA-604-5 Performance: ISO/IEC 11801 Ed.2.2 Kabling: ISO/IEC 24764 Fiber kabeltest: ISO/IEC 14763-3 TIA/EIA-568-C.3 ANSI/TIA-942 10Gbase-SR: IEEE 802.3ae

Packing Units

Enhetstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	1,7 kg
Forpakning 1 høyde	5 cm
Forpakning 1 bredde	19 cm
Forpakning 1 lengde	14 cm

Garantiperiode

Garanti	18 måneder
---------	------------