



Oversikt

Presentasjon	APC Metered by Outlet Rack Power Distribution Units (PDUs) provide individual outlet power metering to enable energy optimization and circuit protection. Current metering provides real-time remote monitoring of connected loads. Metered by Outlet Rack PDUs provide power utilization data to allow Data Center Managers to make informed decisions on load balancing and right sizing IT environments to lower total cost of ownership. Metered by Outlet Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and ultra low profile circuit breakers. Users can access and configure Metered by Outlet Rack PDUs through secure Web, SNMP, or Telnet Interfaces which are complimented by APC Centralized Management platforms using InfraStruxure Central, Operations, Capacity, and Energy Efficiency.
Leveringstid	Usually in Stock

General

Tilgjengelig utstyr	CAN port terminator Installation guide Rack mounting brackets Safety guide Serial configuration cable
---------------------	---

Physical

Farge	Sort
Dybde	5,1 cm
Høyde	182,9 cm
Vekt	6,08 kg
Bredde	5,6 cm

Input

[In] merkestrøm	16 A
Permissible voltage	100...240 V
Input current limits	20 A
Load capacity	3300 VA
Network frequency	50/60 Hz
Plug standard	IEC 60320 C20
Forsyningsspenning	200 V 208 V 230 V

Output

Number of power socket outlets	21 IEC 60320 C13 3 IEC 60320 C19
--------------------------------	-------------------------------------

Conformance

Produktsertifikater	PSE UL listet VCCI klasse A VDE
Standarder	EN 55022 klasse A EN 55024 EN 61000-3-2 EN 61000-3-3 FCC part 15 class A ICES-003

Environmental

Omgivelsestemperatur drift	-5...45 °C
Relativ fuktighet	5...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0,00...15240,00 m

Packing Units

Forpakning 1 vekt	8,35 kg
Forpakning 1 høyde	203,7 cm
Forpakning 1 bredde	16,3 cm
Forpakning 1 lengde	11,7 cm
Antall enheter forpakning 3	48

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	REACH-erklæring
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Blyfri	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Miljøinformasjon	Produktmiljøprofil
Produktets livssyklus	Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt

Garantiperiode

Garanti	2 years repair or replace
---------	---------------------------