

SC450RMI1U

APC Smart-UPS SC 450VA 230V - 1U

Rackmount/Tower



Oversikt



Presentasjon	APC Smart-UPS SC is ideal for small and medium businesses looking to protect networking equipment and point-of-sale (POS) devices from power disturbances and outages. The Smart-UPS SC features network grade protection, hot swap batteries, and built-in data line protection for worry free uninterruptible power protection for increased availability. Built on the same standards as the award-winning Smart-UPS, Smart-UPS SC provides the basic features and manageability needed to protect entry-level applications
Leveringstid	Usually in Stock

General

Inkludert utstyr	User manual Rack mounting brackets Smart UPS signalling RS-232 cable CD with software
Product web sub-family	Entry level
Performance multiplier	1
Number of tare power	14 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
Size UPS version	Internetworking Server Telecom
UPS size	S
Value multiplier	1

Physical

Number of rack unit	1U
Farge	Grå
Dybde	38,3 cm
Høyde	4,4 cm
Montasjeplassering	Front
Mounting preference	Lower
Vekt	10,18 kg
Monteringsmetode	Rack-mounted
Two post mountable	0
USB compatible	No
Bredde	43,2 cm

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	IEC 320 C14
Input voltage limits	151...302 V Justbar 195...265 V
Forsyningsspenning	230 V

Output

Merkeeffekt i W	280 W
Maximum configurable power in W	280 W
Harmonic distortion	Mindre enn 5 % ved full last
Output frequency	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Nb of power socket outlets	4 IEC 320 C13 2 IEC Jumpers
Curve equation	Efficiency
Curve load maximum	100 %
Curve X-axis maximum	100 %
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	450 VA
Merkeeffekt VA	450 VA
Transfer time	4 ms typical : 8 ms maximum

Conformance

Produktsertifikater	C-Tick CE EAC GOST TISI VDE
---------------------	--

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0,00...15240,00 m
Akkustikknivå	38 dBA
Varmeavgivelse	38 Btu/t
Show note OP temperature	No

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	5 t
Number of battery replacement quantity	1
Liquid value	0
Batterispenningen	12 V
Kapasitet på batteri	9,0 Ah
Battery curve	Z
Battery charger power	22 W rated
Battery power in VAH	108 VAh runtime
Batterilevetid	3...5 år
Extended runtime	0

Communications & Management

Ledige plasser	0
Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Optional

Surge Protection and Filtering

Surge energy rate	320 J
Noise suppression	Full time multi-pole noise filtering : 0.7% IEEE surge let-through : zero clamping response time : meets UL 1449
Data line protection	RJ11 2-Way Modem/Fax/DSL splitter with protection (four wire dual lines) RJ45 10/100 Base-T Ethernet protection

Packing Units

Forpakning 1 vekt	11,73 kg
Forpakning 1 høyde	16,4 cm
Forpakning 1 bredde	47,6 cm
Forpakning 1 lengde	58,9 cm
Antall enheter forpakning 3	24

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Miljøinformasjon	Produktmiljøprofil
Produktets livssyklus	Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt

Garantiperiode

Garanti	2 years repair or replace
---------	---------------------------