

AP8941

Rack PDU 2G, Switched, 30A, 200/208V, (21)
C13 & (3) C19 (BEING DISCONTINUED - SEE
APDU9941)



Oversikt

Presentasjon	APC Switched Rack PDUs distribute reliable rack power distribution via a single input with multiple output receptacles. Individual outlet control provides advanced load management. Real-time remote monitoring and user-defined alarms help prevent potential circuit overloads that can cause accidental power loss to critical equipment. Included capabilities include individual remote on/off by outlet, power-on sequencing with time delays, outlet level grouping, and outlet grouping on multiple APC Switched Rack PDUs. Easily access, configure, and manage this metered PDU from remote locations. A network management interface provides standards-based management via Web, SNMP, and Command Line Interface. This Switched PDU from APC provides (21) IEC 60320 C13, (3) IEC 60320 C190 outlets to supply power to rack equipment. User customized alarms and an embedded memory log are included. Volts, amps, real power (kW), and energy (kWh) data is provided to support energy management. An embedded log memory to reports historic metered data. Display details current, power, and voltage measurements and offers local user access. An environmental monitoring port for external temperature/humidity monitoring is available (sensor sold separately model AP9335T or AP9335TH). Easily mount this vertical PDU in racks or enclosures. It occupies zero U of valuable rack space, which allows space for more equipment in the rack. This vertical PDU does not require additional tools to mount into APC NetShelter Enclosures. Enables a quick recovery from overload events and breakers are ultra-low profile. Packaging Includes PDU, Installation guide, Rack Mounting brackets, Safety guide, Serial configuration cable.
Leveringstid	Usually in Stock

General

Tilgjengelig utstyr	Installation guide Rack mounting brackets Serial configuration cable Safety guide
---------------------	--

Physical

Kabellengde	3,05 m
Farge	Sort
Dybde	4,6 cm
Høyde	182,9 cm
Vekt	7,64 kg
Bredde	5,6 cm

Input

[In] merkestrøm	24 A
Max line current	30 A
Input current limits	30 A
Load capacity	4992 VA
Network frequency	50/60 Hz
Plug standard	NEMA L6-30P
Forsyningsspenning	200 V 208 V 230 V

Output

Number of power socket outlets	21 IEC 60320 C13 3 IEC 60320 C19
--------------------------------	-------------------------------------

Conformance

Produktsertifikater	CUL listed PSE UL listet VCCI klasse A
Standarder	FCC part 15 class A ICES-003

Environmental

Omgivelsestemperatur drift	-5...45 °C
Relativ fuktighet	5...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0,00...15240,00 m

Packing Units

Forpakning 1 vekt	10 kg
Forpakning 1 høyde	204 cm
Forpakning 1 bredde	16,5 cm
Forpakning 1 lengde	12,4 cm
Antall enheter forpakning 3	48

Offer Sustainability

Produkts miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Blyfri	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Miljøinformasjon	 Produktmiljøprofil
Produkts livssyklus	 Informasjon Om Levetidsslutt
Optimalisert energieffektivitet	Energieffektivt produkt

Garantiperiode

Garanti	2 years repair or replace
---------	---------------------------