



Oversikt

Presentasjon	Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.
Leveringstid	Usually in Stock

Physical

Kabellengde	3,00 m
Dybde	10,2 cm
Høyde	43,2 cm
Vekt	0,49 kg
Bredde	15,2 cm

Input

Plug standard	IEC 60309 16 A 2P + E
Max line current	16 A
Input current limits	16 A

Output

Max current draw	16 A
Number of power socket outlets	1 IEC 60320 C19
Power cable length	3,05 m

Conformance

Produktsertifikater	VDE
---------------------	-----

Environmental

Omgivelsestemperatur drift	0...70 °C
Relativ fuktighet	20...80 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-25...70 °C
Storage Relative Humidity	20...80 %
Storage altitude	0,00...15240,00 m

Packing Units

Forpakning 1 vekt	0,49 kg
Forpakning 1 høyde	43,2 cm
Forpakning 1 bredde	15,2 cm
Forpakning 1 lengde	10,2 cm
Antall enheter forpakning 3	600

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	REACH-erklæring
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Blyfri	Ja
Miljøinformasjon	Produktmiljøprofil
Produktets livssyklus	Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.

Garantiperiode

Garanti	2 years repair or replace
---------	---------------------------