

AP8716R

Power Cord Kit (6 ea), Locking, C19 to C20 (90 Degree), 1.8m



Oversikt

Presentasjon	Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.
Leveringstid	Usually in Stock

General

Tilgjengelig utstyr	3 left-angle jumper cords 3 right-angle jumper cords
---------------------	---

Physical

Kabellengde	1,83 m
Farge	Sort
Dybde	7 cm
Høyde	30 cm
Vekt	2,16 kg
Bredde	8 cm

Input

Plug standard	IEC 60320 C20
Antall kabler	6
Max line current	16 A
Input current limits	16 A

Output

Max current draw	16 A
Number of power socket outlets	1 IEC 60320 C19
Power cable length	1,83 m

Conformance

Produktsertifikater	CCC CSA PSE UL listet VDE
---------------------	---------------------------------------

Environmental

Omgivelsestemperatur drift	0...75 °C
Relativ fuktighet	20...80 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-25...75 °C
Storage Relative Humidity	20...80 %
Storage altitude	0,00...15240,00 m

Packing Units

Forpakning 1 vekt	2,16 kg
Forpakning 1 høyde	30 cm
Forpakning 1 bredde	8 cm
Forpakning 1 lengde	7 cm
SCC14	10731304279713
Antall enheter forpakning 3	240

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Blyfri	Ja
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.

Garantiperiode

Garanti	2 years repair or replace
---------	---------------------------