



Oversikt

Presentasjon	APC Metered by Outlet with Switching Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and individual outlet power metering. Remote outlet level controls allow power on/off functionality for power recycling to reboot locked-up equipment and to avoid unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, and locking IEC receptacles. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.
Leveringstid	Usually in Stock

General

Tilgjengelig utstyr	CAN port terminator Installation guide Rack mounting brackets Safety guide Serial configuration cable
---------------------	---

Physical

Kabellengde	1,83 m
Farge	Sort
Dybde	5,1 cm
Høyde	182,9 cm
Vekt	8,23 kg
Bredde	5,6 cm

Input

[In] merkestrøm	16 A
Max line current	16 A
Input current limits	16 A
Load capacity	11000 VA
Network frequency	50/60 Hz
Plug standard	IEC 60309 16 A 3P + N + PE IEC 60309 20 A 3P + N + PE
Forsyningsspenning	400 V 3 phases

Output

Number of power socket outlets	21 IEC 60320 C13 3 IEC 60320 C19
--------------------------------	-------------------------------------

Conformance

Produktsertifikater	CUL listed UL listet VDE
Standarder	EN 55022 klasse A EN 55024 EN 61000-3-2 EN 61000-3-3 FCC part 15 class A ICES-003

Environmental

Omgivelsestemperatur drift	-5...45 °C
Relativ fuktighet	5...95 %
Driftshøyde	0...10000 ft
Storage Relative Humidity	5...95 %
Storage altitude	0,00...15240,00 m

Packing Units

Forpakning 1 vekt	10,5 kg
Forpakning 1 høyde	203,8 cm
Forpakning 1 bredde	16,2 cm
Forpakning 1 lengde	11,7 cm

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Blyfri	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt

Garantiperiode

Garanti	2 years repair or replace
---------	---------------------------