



Oversikt

Presentasjon	APC Metered by Outlet with Switching Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and individual outlet power metering. Remote outlet level controls allow power on/off functionality for power recycling to reboot locked-up equipment and to avoid unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, and locking IEC receptacles. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.
Leveringstid	Usually in Stock

General

Tilgjengelig utstyr	CAN port terminator Installation guide Rack mounting brackets Safety guide Serial configuration cable
---------------------	---

Physical

Kabellengde	3,00 m
Farge	Sort
Dybde	5,1 cm
Høyde	182,9 cm
Vekt	8,23 kg
Bredde	5,6 cm

Input

[In] merkestrøm	24 A
Permissible voltage	200...240 V
Max line current	30 A
Input current limits	30 A
Load capacity	4992 VA
Network frequency	50/60 Hz
Plug standard	NEMA L6-30P
Forsyningsspenning	200 V 208 V 230 V

Output

Number of power socket outlets	21 IEC 60320 C13 3 IEC 60320 C19
--------------------------------	-------------------------------------

Conformance

Produktsertifikater	CUL listed PSE UL listet VCCI klasse A
Standarder	FCC part 15 class A ICES-003

Environmental

Omgivelsestemperatur drift	-5...45 °C
Relativ fuktighet	5...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0,00...15240,00 m

Packing Units

Forpakning 1 vekt	10,5 kg
Forpakning 1 høyde	203,8 cm
Forpakning 1 bredde	16,2 cm
Forpakning 1 lengde	11,8 cm
Antall enheter forpakning 3	48

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Blyfri	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt
Optimalisert energieffektivitet	Energieffektivt produkt

Garantiperiode

Garanti	2 years repair or replace
---------	---------------------------