



Oversikt

Leveringstid

Usually in Stock



General

Tilgjengelig utstyr	Installation guide Rack mounting brackets
---------------------	--

Physical

Kabellengde	3,66 m
Farge	Sort
Dybde	5,7 cm
Høyde	4,4 cm
Vekt	2,5 kg
Bredde	44,7 cm

Input

[In] merkestrøm	16 A
Input current limits	20 A
Load capacity	3328 VA
Network frequency	50/60 Hz
Plug standard	NEMA L6-20P
Forsyningsspenning	200 V 208 V 230 V

Output

Number of power socket outlets	12 IEC 60320 C13
--------------------------------	------------------

Conformance

Produktsertifikater	CUL listed UL listed
Standarder	UL 60950

Environmental

Omgivelsestemperatur drift	0...45 °C
Relativ fuktighet	0...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0,00...15240,00 m

Packing Units

Forpakning 1 vekt	3,64 kg
Forpakning 1 høyde	7 cm
Forpakning 1 bredde	46,4 cm
Forpakning 1 lengde	22,9 cm

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	REACH-erklæring
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Blyfri	Ja
Optimalisert energieffektivitet	Energieffektivt produkt

Garantiperiode

Garanti	2 years repair or replace
---------	---------------------------