



Oversikt

Presentasjon

APC Metered Rack PDUs distribute reliable rack power distribution via a single input with multiple output receptacles. Real-time remote monitoring and user-defined alarms help prevent potential circuit overloads that can cause accidental power loss to critical equipment. Easily access, configure, and manage this metered PDU from remote locations. A network management interface provides standards-based management via Web, SNMP, and Command Line Interface. This Metered PDU from APC provides (36) IEC 60320 C13 and (6) IEC 60320 C19 outlets to supply power to rack equipment. Locking IEC receptacles enable locking power cord compatibility to reduce the probability of accidentally disconnecting cords and dropping loads. Volts, amps, real power (kW), and energy (kWh) data is provided to support energy management. An embedded log memory to reports historic metered data. Display details current, power, and voltage measurements and offers local user access. An environmental monitoring port for external temperature/humidity monitoring is available (sensor sold separately model AP9335T or AP9335TH). Easily mount this vertical PDU in racks or enclosures. It occupies zero U of valuable rack space, which allows space for more equipment in the rack. This vertical PDU does not require additional tools to mount into APC NetShelter Enclosures. Enables a quick recovery from overload events and breakers are ultra-low profile. Packaging Includes PDU, Installation guide, Rack Mounting brackets, Safety guide, Serial configuration cable.

Leveringstid

Usually in Stock

General

Tilgjengelig utstyr	Installation guide Rack mounting brackets Serial configuration cable Safety guide
---------------------	--

Physical

Kabellengde	3,00 m
Farge	Sort
Dybde	4,4 cm
Høyde	179,1 cm
Vekt	6,84 kg
Bredde	5,6 cm

Input

[In] merkestrøm	24 A
Permissible voltage	200...240 V
Input current limits	30 A
Load capacity	4992 VA
Network frequency	50/60 Hz

Plug standard	NEMA L6-30P
Forsyningsspenning	200 V 208 V

Output

Number of power socket outlets	36 IEC 60320 C13 6 IEC 60320 C19
--------------------------------	-------------------------------------

Conformance

Produktsertifikater	METI Denan PSE VDE
Standarder	CSA C22.2 No 60950 IEC 60950 UL 60950-1

Environmental

Omgivelsestemperatur drift	-5...45 °C
Relativ fuktighet	5...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0,00...15240,00 m

Packing Units

Forpakning 1 vekt	8,47 kg
Forpakning 1 høyde	200 cm
Forpakning 1 bredde	16,2 cm
Forpakning 1 lengde	10,7 cm
Antall enheter forpakning 3	48

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	REACH-erklæring
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Blyfri	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Miljøinformasjon	Produktmiljøprofil
Produktets livssyklus	Informasjon Om Levetidsslutt
Optimalisert energieffektivitet	Energieffektivt produkt

Garantiperiode

Garanti	2 years repair or replace
---------	---------------------------