



Oversikt

Presentasjon	APC Basic Rack PDUs distribute reliable rack power distribution via a single input with multiple output receptacles. Easily mount this vertical PDU in racks or enclosures. It occupies zero U of valuable rack space, which allows space for more equipment in the rack. This vertical PDU does not require additional tools to mount into APC NetShelter Enclosures. Enables a quick recovery from overload events. Packaging Includes PDU, Installation guide, Rack Mounting brackets, Toolless Mounting Kit.
Leveringstid	Usually in Stock

General

Tilgjengelig utstyr	Installation guide Rack mounting brackets Toolless mounting kit
---------------------	---

Physical

Kabellengde	3,05 m
Farge	Sort
Dybde	4,4 cm
Høyde	161,9 cm
Vekt	5,57 kg
Bredde	5,6 cm

Input

[In] merkestrøm	24 A
Input current limits	30 A
Load capacity	4992 VA
Network frequency	50/60 Hz
Plug standard	NEMA L6-30P
Forsyningsspenning	200 V 208 V 230 V

Output

Number of power socket outlets	20 IEC 60320 C13 4 IEC 60320 C19
--------------------------------	-------------------------------------

Conformance

Produktsertifikater	CUL listed METI Denan PSE UL listet
Standarder	CSA C22.2 No. 60950-1-03 UL 60950-1

Environmental

Omgivelsestemperatur drift	0...45 °C
Relativ fuktighet	0...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0,00...15240,00 m

Packing Units

Forpakning 1 vekt	6,48 kg
Forpakning 1 høyde	212,1 cm
Forpakning 1 bredde	15,2 cm
Forpakning 1 lengde	12,7 cm
Antall enheter forpakning 3	42

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Blyfri	Ja
Optimalisert energieffektivitet	Energieffektivt produkt

Garantiperiode

Garanti	2 years repair or replace
---------	---------------------------