



Oversikt

Leveringstid

Usually in Stock



General

Tilgjengelig utstyr	Installation guide Rack mounting brackets Brukermanual
---------------------	--

Physical

Kabellengde	3,66 m
Farge	Sort
Dybde	7,7 cm
Høyde	4,4 cm
Vekt	2,55 kg
Bredde	44,5 cm

Input

[In] merkestrøm	24 A
Permissible voltage	200...240 V
Max line current	30 A
Input current limits	30 A
Load capacity	4992 VA
Network frequency	50/60 Hz
Plug standard	NEMA L6-30P
Forsyningsspenning	200 V 208 V 230 V

Output

Number of power socket outlets	10 IEC 60320 C13
--------------------------------	------------------

Conformance

Produktsertifikater	CUL listed PSE UL listet
Standarder	UL 60950

Environmental

Omgivelsestemperatur drift	−5...45 °C
Relativ fuktighet	5...95 %
Driftshøyde	0...15000 ft
Omgivelsestemperatur for lagring	−25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0,00...15240,00 m

Packing Units

Forpakning 1 vekt	3,64 kg
Forpakning 1 høyde	17,1 cm
Forpakning 1 bredde	48,3 cm
Forpakning 1 lengde	17,4 cm
Antall enheter forpakning 3	1

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Blyfri	Ja
Optimalisert energieffektivitet	Energieffektivt produkt

Garantiperiode

Garanti	2 years repair or replace
---------	---------------------------