



Oversikt

Presentasjon	APC Metered Rack Power Distribution Units (PDUs) provide active metering to enable energy optimization and circuit protection. User-defined alarm thresholds mitigate risk with real-time local and remote alerts to warn of potential circuit overloads. Metered Rack PDUs provide power utilization data to allow Data Center Managers to make informed decisions on load balancing and right sizing IT environments to lower total cost of ownership. Metered Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and ultra low profile circuit breakers. Users can access and configure Metered Rack PDUs through secure Web, SNMP, or Telnet Interfaces which are complimented by APC Centralized Management platforms using InfraStruxure Central, Operations, Capacity, and Energy Efficiency.
Leveringstid	Usually in Stock

General

Tilgjengelig utstyr	Installation guide Rack mounting brackets Serial configuration cable Safety guide
---------------------	--

Physical

Kabellengde	1,83 m
Farge	Sort
Dybde	5,1 cm
Høyde	182,9 cm
Vekt	10,1 kg
Bredde	5,6 cm

Input

[In] merkestrøm	32 A
Input current limits	40 A
Load capacity	23000 VA
Network frequency	50/60 Hz
Plug standard	IEC 60309 60 A 3P + N + E
Forsyningsspenning	400 V 3 phases

Output

Number of power socket outlets	30 IEC 60320 C13 12 IEC 60320 C19
--------------------------------	--------------------------------------

Conformance

Produktsertifikater	CUL listed UL listed VCCI klasse A
Standarder	EN 55022 klasse A EN 55024 EN 61000-3-2 EN 61000-3-3 FCC part 15 class A ICES-003

Environmental

Omgivelsestemperatur drift	0...55 °C
Relativ fuktighet	5...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0,00...15240,00 m

Packing Units

Forpakning 1 vekt	14,05 kg
Forpakning 1 høyde	214,9 cm
Forpakning 1 bredde	22,1 cm
Forpakning 1 lengde	11,2 cm

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Blyfri	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt
Optimalisert energieffektivitet	Energieffektivt produkt

Garantiperiode

Garanti	2 years repair or replace
---------	---------------------------