



Teknisk informasjon

Serie	Masterpact
Produkt eller type komponent	Application
Application description	Trip fault WFC
Kompatibel med	Masterpact MTZ1 circuit breaker Masterpact MTZ2 circuit breaker Masterpact MTZ3 circuit breaker
Service description	Sampling period of 512 micro seconds in case of trip of LSI or G protection Allows to log automatically five cycles of phase and neutral currents Records the following status: circuit breaker open/closed/trip and ZSI signals Display one cycle before the fault and 4 cycles after
Service benefits	Help to understand the potential damage on the installation Support analysis of global behaviour of the circuit breaker in the power system Help to understand the nature and gravity of the fault (amplitude and duration)
Energiledelse	Diagnostics and maintenance ,crisis management (option)

Komplementær

Software navn	EcoStruxure Power Device
---------------	--------------------------

Packing Units

Forpakning 1 vekt	0,200 kg
Forpakning 1 høyde	0,100 dm
Forpakning 1 bredde	0,400 dm
Forpakning 1 lengde	0,300 dm

Offer Sustainability

REACH-regelverk	REACH-erklæring
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Kinas RoHS-forskrift	Kinas RoHS-Erklæring

Garantiperiode

Garanti	18 måneder
---------	------------