



Oversikt

Presentasjon	High-efficiency 3-phase UPS that features advanced product features, competitive specifications, and robust electrical design, making business continuity easy in the data center or electrical room. This is an exceptionally easy to install, operate, maintain, and service 15 kVA UPS, ideal for small and medium businesses. Includes dust filter and conformance-coated boards for harsh environments. This UPS is supplied without batteries, so you can easily customize the battery solution.
Leveringstid	Usually Ships within 6 Weeks

General

Inkludert utstyr	Dust filter Installation guide
UPS size	WS

Physical

Farge	Hvit (RAL 9003)
Dybde	70 cm
Høyde	53 cm
Vekt	36 kg
USB compatible	Yes
Bredde	25 cm

Input

Network frequency	45...65 Hz
Inputvolt_other	380 V 415 V
Maximum input current	28 A
Input harmonic distortion	Less than 5 % for full load
Forsyningsspenning	3 faser
Cos phi	0,99

Output

Merkeeffekt i W	15000 W
Maximum configurable power in W	15000 W
Harmonic distortion	Mindre enn 3 %
Output frequency	50 Hz sync to mains 60 Hz sync to mains
Outputvolt_other	220 V 240 V
Crest faktor	3:1
UPS type	Double conversion online
Output overload operation	10 minutes at 125% and 60 seconds at 150%
Curve equation	Efficiency
Curve fixed loss	0,0079
Curve load maximum	100 %

Curve load minimum	1 %
Curve proportional loss	0,0222
Curve square loss	0,0298
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit to measured efficiency data. All measurements taken in normal operating mode, at typical environmental conditions, with 400V 50Hz input and 400V 50Hz balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	15000 VA
Merkeffekt VA	15000 VA

Conformance

Produktsertifikater	CE EAC RCM
Standarder	IEC 62040-1-1 IEC 62040-2 IEC 62040-3 IEC 62040-4 ISTA 2B

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 % non-condensing
Driftshøyde	0...3281 ft
Omgivelsestemperatur for lagring	-15...40 °C
Storage Relative Humidity	0...95 % Ikke-kondenserende
Storage altitude	0,00...15240,00 m
Akkustikknivå	60 dBA
Varmeavgivelse	516 Btu/t
Show note OP temperature	No
IP-grad	IP20

Batteries & Runtime

Batteritype	External battery system
Number of battery filled slots	0
Number of battery free slots	0
Liquid value	0
Maximum short-circuit current	10 kA
Battery curve	B

Packing Units

Forpakning 1 vekt	49,895 kg
Forpakning 1 høyde	77,191 cm
Forpakning 1 bredde	40,005 cm
Forpakning 1 lengde	85,700 cm

Offer Sustainability

EU RoHS-direktiv	Proaktivt i samsvar (Produktet inngår ikke i EUs RoHS direktivet) EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Kinas RoHS-forskrift	Kinas RoHS-Erklæring
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt

Garantiperiode

Garanti	1 year on-site repair or replace with factory authorized Start-Up
---------	---