



Teknisk informasjon

Produktspekter	Altivar Process ATV600
Produkt eller type komponent	Frekvensomformer
Produktspesifikk applikasjon	Prosess og verktøy
Kortnavn utstyr	ATV630
Variant	Standard versjon
Produsert i	Synchronous motors Asynkrone motorer
EMC filter	Uten EMC filter
IP-grad	IP00 conforming to IEC 61800-5-1 IP00 conforming to IEC 60529 IP21 (med kit VW3A9705) i samsvar med IEC 61800-5-1 IP21 (med kit VW3A9705) i samsvar med IEC 60529
Kjølemetode	Tvangsstyrt konveksjon
Nettfrekvens	50...60 Hz - 5...5 %
[Us] matespenning	200...240 V - 15...10 %
Motoreffekt kW	75 kW (normal duty) 55 kW (heavy duty)
Motoreffekt hk	100 Hp normal duty 75 hp heavy duty
Nettstrøm	256 A på 200 V (normal duty) 215 A på 240 V (normal duty) 189 A på 200 V (heavy duty) 161 A på 240 V (heavy duty)
Maks kortslutningsnivå Isc	50 kA
Tilsynelatende effekt	83,7 KVA på 240 V (normal duty) 61,1 kVA på 240 V (heavy duty)
Nominell utgangsstrøm	211 A på 2,5 kHz for heavy duty 282 A på 2,5 kHz for normal duty
Maksimal transient strøm	310,2 A under 60 s (normal duty) 316,5 A under 60 s (heavy duty)
Motorkontroll metode	Konstant dreiemoment standard Optimalisert dreiemoment-modus Variabelt dreiemoment standard
Synchronous motor control profile	Permanent magnet motor Synchronous reluctance motor
Output frequency	0,0001...0,5 kHz
Speed drive utgangsfrekvens	0,1...599 Hz
Nominell svitsjefrekvens	2,5 kHz
Switching frequency	2,5...8 kHz with derating factor 2...8 kHz adjustable
Sikkerhetsfunksjon	STO (safe torque off) SIL 3
Diskrét inngangs logikk	16 forhåndsinnstilte hastigheter

Informasjonen som gis i denne dokumentasjonen inneholder generelle beskrivelser og/eller tekniske egenskaper av ytelsen til produktene i dokumentet. Denne dokumentasjonen er ikke ment som en erstatning for, og må ikke brukes til å bestemme egnethet eller påliteligheten til disse produktene for spesifikke brukerapplikasjoner. Enhver bruker eller integrator er ansvarlig for å utføre egnethet, analyse og testing av produktene med hensyn til aktuell bruk. Verken Schneider Electric Industries SAS eller noen av deres datterselskaper skal være ansvarlig for misbruk av informasjonen som finnes her.

Kommunikasjonsprotokoll	Modbus serial ETHERNET Modbus TCP
Funksjonskort	Slot A: kommunikasjons modul, Profibus DP V1 Slot A: kommunikasjons modul, Profinet Slot A: kommunikasjons modul, DeviceNet Slot A: kommunikasjons modul, Modbus TCP / Ethernet / IP Slot A: kommunikasjons modul, CANopen daisy chain RJ45 Slot A: kommunikasjons modul, CANopen SUB-D 9 Slot A: kommunikasjons modul, CANopen skrueterminaler Slot A/slot B: digital og analog I/O utvidelses modul Slot A/slot B: output relay extension module Slot A: kommunikasjons modul, Ethernet IP / Modbus TCP / MD-Link Kommunikasjons modul, BACnet MS/TP Kommunikasjons modul, Ethernet Powerlink

Komplementær

Monteringsmetode	Veggmontering
Utgangsspenning	<= strømforsyningsspenning
Tillatt korttidstrøm	1.1 x In during 60 s (normal duty) 1.5 x In during 60 s (heavy duty)
Motor slip kompensasjon	Automatic whatever the load Not available in permanent magnet motor law Can be suppressed Justrbar
Akselerasjons- og retardasjonsramper	Linear adjustable separately from 0.01...9999 s
Bremsing til stillstand	Ved DC-bremsing
Beskyttelsestype	Thermal protection: motor Safe torque off: Motor Motor phase break: motor Thermal protection: drive Safe torque off: drive Overoppvarming: drive Overcurrent between output phases and earth: drive Overload of output voltage: drive Kortslutningsvern: drive Mot brudd av motorfase: drive Overvoltages on the DC bus: drive Line supply overvoltage: drive Line supply undervoltage: drive Line supply phase loss: drive Overspeed: drive Break on the control circuit: drive
Frekvensoppløsning	Display unit: 0.1 Hz Analog input: 0.012/50 Hz
Elektrisk tilkobling	Control: removable screw terminals 0.5...1.5 mm ² /AWG 20...AWG 16 Line side: screw terminal 2 x 95...3 x 120 mm ² /2 x AWG 3/0...2 x 300 kcmil Motor: screw terminal 2 x 95...3 x 120 mm ² /2 x AWG 3/0...2 x 300 kcmil
Type konnektor	RJ45 (on the remote graphic terminal) for Ethernet/Modbus TCP RJ45 (on the remote graphic terminal) for Modbus serial
Exchange-modus	Half duplex, full duplex, autonegotiation Ethernet/Modbus TCP
Antall adresser	1...247 for Modbus serial
Tilgangsmetode	Slave Modbus TCP
Supply	External supply for digital inputs: 24 V DC (19...30 V), <1.25 mA, protection type: overload and short-circuit protection Internal supply for reference potentiometer (1 to 10 kOhm): 10.5 V DC +/- 5 %, <10 mA, protection type: overload and short-circuit protection Internal supply for digital inputs and STO: 24 V DC (21...27 V), <200 mA, protection type: overload and short-circuit protection
Lokal varsling	3 LEDs for local diagnostic 3 LEDs (dual colour) for embedded communication status 4 LEDs (dual colour) for communication module status Tilstedeværelse av spenning: 1 LED (rødt)
Bredde	320 mm
Høyde	852 mm
Dybde	390 mm

Vekt	84 kg
Antall analoge innganger	3
Analogue input type	AI1, AI2, AI3 software-configurable voltage: 0...10 V DC, impedance: 30 kOhm, resolution 12 bits AI1, AI2, AI3 software-configurable current: 0...20 mA/4...20 mA, impedance: 250 Ohm, resolution 12 bits
Discrete input number	8
Discrete input type	DI1...DI6 programmable, 24 V DC (≤ 30 V), impedance: 3.5 kOhm DI5, DI6 programmable as pulse input: 0...30 kHz, 24 V DC (≤ 30 V) STOA, STOB safe torque off, 24 V DC (≤ 30 V), impedance: > 2.2 kOhm
Input compatibility	DI1...DI6: discrete input level 1 PLC conforming to EN/IEC 61131-2 DI5, DI6: discrete input level 1 PLC conforming to IEC 65A-68 STOA, STOB: discrete input level 1 PLC conforming to EN/IEC 61131-2
Diskrét inngangs logikk	Positive logic (source) (DI1...DI6), < 5 V (state 0), > 11 V (state 1) Negative logic (sink) (DI1...DI6), > 16 V (state 0), < 10 V (state 1) Positive logic (source) (DI5, DI6), < 0.6 V (state 0), > 2.5 V (state 1) Positive logic (source) (STOA, STOB), < 5 V (state 0), > 11 V (state 1)
Analog utgangsnummer	2
Analog utgangstype	Software-configurable voltage AO1, AO2: 0...10 V DC impedance 470 Ohm, resolution 10 bits Software-configurable current AO1, AO2: 0...20 mA, resolution 10 bits
Sampling varighet	2 Ms ± 0.5 ms (DI1...DI4) - discrete input 5 Ms ± 1 ms (DI5, DI6) - discrete input 5 Ms ± 0.1 ms (AI1, AI2, AI3) - analog input 10 ms ± 1 ms (AO1) - analog output
Nøyaktighet	± 0.6 % AI1, AI2, AI3 for a temperature variation 60 °C analog input ± 1 % AO1, AO2 for a temperature variation 60 °C analog output
Lineær feil	AI1, AI2, AI3: ± 0.15 % of maximum value for analog input AO1, AO2: ± 0.2 % for analog output
Relé utgang nummer	3
Reléutgangstype	Configurable relay logic R1: fault relay NO/NC electrical durability 100000 cycles Configurable relay logic R2: sequence relay NO electrical durability 100000 cycles Configurable relay logic R3: sequence relay NO electrical durability 100000 cycles
Refresh time	Relay output (R1, R2, R3): 5 ms (± 0.5 ms)
Minimum brytestrøm	Relay output R1, R2, R3: 5 mA at 24 V DC
Maximum svitsjestrøm	Relay output R1, R2, R3 on resistive load, $\cos \phi = 1$: 3 A at 250 V AC Relay output R1, R2, R3 on resistive load, $\cos \phi = 1$: 3 A at 30 V DC Relay output R1, R2, R3 on inductive load, $\cos \phi = 0.4$ and L/R = 7 ms: 2 A at 250 V AC Relay output R1, R2, R3 on inductive load, $\cos \phi = 0.4$ and L/R = 7 ms: 2 A at 30 V DC
Skille	Between power and control terminals
Variable speed drive application selection	Building - HVAC Compressor centrifugal Food and beverage processing Annen applikasjon Mining mineral and metal Vifte Mining mineral and metal Pumpe Olje og gass Vifte Vann og avløpsvann Annen applikasjon Building - HVAC Skruekompressor Food and beverage processing Pumpe Food and beverage processing Vifte Food and beverage processing Automasjon Olje og gass Electro submersible pump (ESP) Olje og gass Water injection pump Olje og gass Flybensin pumpe Olje og gass Compressor for refinery Vann og avløpsvann Sentrifuge pumpe Vann og avløpsvann Positive displacement pump Vann og avløpsvann Electro submersible pump (ESP) Vann og avløpsvann Skruepumpe Vann og avløpsvann Lobe compressor Vann og avløpsvann Skruekompressor Vann og avløpsvann Compressor centrifugal Vann og avløpsvann Vifte Vann og avløpsvann Conveyor Vann og avløpsvann Mikser
Motor power range AC-3	55...100 kW at 200...240 V 3 phases

Miljø

Isolasjonsmotstand	> 1 MOhm 500 V DC for 1 minute to earth
Noise level	69,9 dB i samsvar med 86/188/EEC
Volum av kjøleluft	600 m3/t
Driftsposisjon	Vertikal +/- 10 grader
Maximum THDI	<48 % full load conforming to IEC 61000-3-12
Elektromagnetisk kompatibilitet	Electrostatic discharge immunity test level 3 conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test level 3 conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4 1.2/50 µs - 8/20 µs surge immunity test level 3 conforming to IEC 61000-4-5 Conducted radio-frequency immunity test level 3 conforming to IEC 61000-4-6
Forurensninggrad	2 i samsvar med EN/IEC 61800-5-1
Vibrasjonsmotstand	1.5 mm peak to peak (f= 2...13 Hz) conforming to IEC 60068-2-6 1 gn (f= 13...200 Hz) i samsvar med IEC 60068-2-6
Støtmotstand	15 gn for 11 ms i samsvar med IEC 60068-2-27
Relativ fuktighet	5...95 % without condensation conforming to IEC 60068-2-3
Omgivelsestemperatur for drift	-15...50 °C (uten lastreduksjon) 50...60 °C (med belastningsfaktor)
Omgivelsestemperatur for lagring	-40...70 °C
Operating altitude	<= 1000 m uten lastreduksjon 1000...4800 m with current derating 1 % per 100 m
Standarder	UL 508C EN/IEC 61800-3 Miljø 1 kategori C2 EN/IEC 61800-3 Miljø 2 kategori C3 EN/IEC 61800-3 EN/IEC 61800-5-1 IEC 61000-3-12 IEC 60721-3 IEC 61508 IEC 13849-1
Produktsertifikater	UL DNV-GL TÜV CSA ATEX zone 2/22 ATEX INERIS
Merking	CE

Packing Units

Forpakning 1 vekt	125,000 kg
Forpakning 1 høyde	6,480 dm
Forpakning 1 bredde	4,650 dm
Forpakning 1 lengde	10,250 dm

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
EU RoHS-direktiv	Proaktivt i samsvar (Produktet inngår ikke i EUs RoHS direktivet) EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Kinas RoHS-forskrift	Kinas RoHS-Erklæring
Miljøinformasjon	Produktmiljøprofil
Produktets livssyklus	Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Oppgraderbarhet	Oppgraderte Komponenter Tilgjengelig

Garantiperiode

Garanti

18 måneder