



Teknisk informasjon

Serie	TeSys
Produktnavn	TeSys CAD
Produkt eller type komponent	Kontroll reléee
Kortnavn utstyr	CAD
Contact application	Styrekrets

Komplementær

Driftskategori	AC-15 AC-14 DC-13
Kontakttype	5 NO
[Ue] merkespenning	≤ 690 V AC 25...400 Hz
Kontrollkretstype	DC low consumption
Styrespenning	24 V DC
[Uimp] Nominell impuls spenning	6 kV i samsvar med IEC 60947
[Ith] fri luft termisk strøm	10 A (at 60 °C)
Irms rated making capacity	140 A AC conforming to IEC 60947-5-1 250 A DC conforming to IEC 60947-5-1
[Icw] kort-tids/kortslutnings merkestrøm	100 A - 1 s 120 A - 500 ms 140 A - 100 ms
Sikringsstørrelse	10 A gG conforming to IEC 60947-5-1
[Ui] isolasjonsspenning	600 V UL certified 600 V CSA certified 690 V conforming to IEC 60947-5-1
Montering	Skinne Plate
Tilkoblingsklemmer	Screw clamp terminals 1 cable(s) 1...4 mm ² flexible without cable end Screw clamp terminals 2 cable(s) 1...4 mm ² flexible without cable end Screw clamp terminals 1 cable(s) 1...4 mm ² flexible with cable end Screw clamp terminals 2 cable(s) 1...2.5 mm ² flexible with cable end Screw clamp terminals 1 cable(s) 1...4 mm ² solid without cable end Screw clamp terminals 2 cable(s) 1...4 mm ² solid without cable end
Tiltrekningsmoment	1.2 N.M - on screw clamp terminals - with screwdriver Philips No 2 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm
Control circuit voltage limits	0,1 - 0,25 U _c -40...70 °C drop-out DC 0,7 - 1,25 U _c -40...60 °C operasjonell DC 1...1.25 U _c 60...70 °C operasjonell DC
Driftstid	65...88 ms coil energisation and NO closing 14...25 ms coil de-energisation and NO opening
Mekanisk levetid	30 Mcycles
Bruksområde	180 cyc/mn
Tidskonstant	40 ms
Inrush power in W	2.4 W (at 20 °C)
Hold-in strømforbruk i W	2.4 W at 20 °C
Minimum switching voltage	17 V
Minimum brytestrøm	5 mA

Non-overlap time	1,5 Ms on energisation mellom NC og NO-kontakt 1,5 ms on de-energisation mellom NC og NO-kontakt
Isolasjonsmotstand	> 10 MOhm
Mekanisk robusthet	Shocks control relay open: 10 Gn for 11 ms conforming to IEC 60068-2-27 Shocks control relay closed: 15 Gn for 11 ms conforming to IEC 60068-2-27 Vibrations control relay open: 2 Gn, 5...300 Hz conforming to IEC 60068-2-6 Vibrations control relay closed: 4 Gn, 5...300 Hz conforming to IEC 60068-2-6
Høyde	77 mm
Bredde	45 mm
Dybde	93 mm
Vekt	0,58 kg

Miljø

Standarder	BS 4794 EN 60947-5 IEC 60947-5-1 NF C 63-140 VDE 0660
Produktsertifikater	CSA UL
IP-grad	IP2x conforming to VDE 0106
Protective treatment	TH i samsvar med IEC 60068
Omgivelsestemperatur for drift	-40...60 °C 60...70 °C med effektreduksjon
Omgivelsestemperatur for lagring	-60...80 °C
Operating altitude	0...3000 m

Packing Units

Enhetstype forpakning 1	PCE
Antall enheter forpakning 1	1
Forpakning 1 vekt	531 g
Forpakning 1 høyde	5,2 cm
Forpakning 1 bredde	9,2 cm
Forpakning 1 lengde	11,2 cm

Offer Sustainability

EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Kinas RoHS-forskrift	 Kinas RoHS-Erklæring
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.

Garantiperiode

Garanti	18 months
---------	-----------