

## H2,5/15T GR

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)



- supplied loose in polybag
- DIN colour code
- other colour code

### General ordering data

|            |                                                |
|------------|------------------------------------------------|
| Version    | Wire-end ferrule, insulated, 10 mm, 8 mm, grey |
| Order No.  | <a href="#">9021070000</a>                     |
| Type       | H2,5/15T GR                                    |
| GTIN (EAN) | 4008190128944                                  |
| Qty.       | 500 pc(s).                                     |
| Packaging  | loose                                          |

## H2,5/15T GR

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |
|------------|---------|
| Net weight | 0.104 g |
|------------|---------|

## Technical data

|                        |                                            |         |           |
|------------------------|--------------------------------------------|---------|-----------|
| Description of article | Wire end ferrule with plastic collar, grey | Version | insulated |
|------------------------|--------------------------------------------|---------|-----------|

## Wire-end ferrules

|                                         |         |                               |               |
|-----------------------------------------|---------|-------------------------------|---------------|
| Collar diameter (D2)                    | 4.4 mm  | Colour code                   | Telemecanique |
| Conductor cross-section                 | 2.5 Nm  | Contact surface diameter (D1) | 2.2 mm        |
| Contact surface length (L2)             | 8 mm    | L1 in mm                      | 15 mm         |
| Metal sleeve thickness (S1)             | 0.15 mm | Military designation          | T 20A 023 A   |
| Plastic collar thickness (S2)           | 0.25 mm | Stripping length              | 10 mm         |
| Wire connection cross section AWG, max. | AWG 14  |                               |               |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0    | EC000005    |
| ETIM 8.0    | EC000005    | ECLASS 9.0  | 27-40-02-01 |
| ECLASS 9.1  | 27-40-02-01 | ECLASS 10.0 | 27-40-02-01 |
| ECLASS 11.0 | 27-40-02-01 |             |             |

## Approvals

Approvals



|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E499744 |

## Downloads

|                    |                                                                                          |
|--------------------|------------------------------------------------------------------------------------------|
| Engineering Data   | <a href="#">STEP</a>                                                                     |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                                                 |
| User Documentation | <a href="#">Technical information - EN</a><br><a href="#">Technical information - DE</a> |
| Catalogues         | <a href="#">Catalogues in PDF-format</a>                                                 |
| Brochures          |                                                                                          |

## H2,5/15T GR

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

### Drawing

