

WSI 4**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image****Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

Version	W-Series, Fuse terminal, Rated cross-section: 4 mm ² , Screw connection
Order No.	1886580000
Type	WSI 4
GTIN (EAN)	4032248492060
Qty.	50 pc(s).

WSI 4

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	42.5 mm	Depth (inches)	1.673 °C
Depth including DIN rail	54 mm	Height	50.7 mm
Height (inches)	1.996 °C	Width	8 mm
Width (inches)	0.315 °C	Net weight	11.08 g

Temperatures

Storage temperature	-25 °C...55 °C	Continuous operating temp., min.	-50 °C
Continuous operating temp., max.	120 °C		

Material data

Material	Wemid	Colour	black
UL 94 flammability rating	V-0		

System specifications

Version	Screw connection, Fuse isolator, in closed state	End cover plate required	No
Number of potentials	1	Number of levels	1
Number of clamping points per level	2	Number of potentials per tier	1
Levels cross-connected internally	No	PE connection	No
Rail	TS 35	N-function	No
PE function	No	PEN function	No

2 clampable conductors (H05V/H07V) with equal cross-section (rated connection)

Cross-section for connected wire, solid, two clampable wires, max.	1.5 Nm	Cross-section for connected wire, solid, two clampable wires, min.	0.5 Nm
Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, 2 clampable wires, max.	1.5 Nm	Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, 2 clampable wires, min.	0.5 Nm
Wire connection cross section, finely stranded, two clampable wires, min.	0.5 Nm	Wire cross-section, finely stranded, two clampable wires, max.	1.5 Nm

Additional technical data

Number of similar terminals	1	Type of mounting	Snap-on
-----------------------------	---	------------------	---------

CSA rating data

Certificate No. (CSA)	200039-1575489	Current size C (CSA)	15 A
Voltage size C (CSA)	300 V	Wire cross section max. (CSA)	12 AWG
Wire cross section min. (CSA)	30 AWG		

Conductors for clamping (rated connection)

Blade size	0.6 x 3.5 mm
------------	--------------

WSI 4

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Clampable conductor	Connection specification		Screw connection	
	Cross-section for conductor connection	Type	solid, H05(07) V-U	
		min.	0.5 Nm	
		max.	4 Nm	
		nominal	4 Nm	
	wire end ferrule	Stripping length	min.	8 mm
			max.	8 mm
			nominal	8 mm
		Tightening torque	min.	0.4 inch
			max.	0.4 inch
		Recommended wire-end ferrule		
	Connection specification		Screw connection	
	Cross-section for conductor connection	Type	stranded, H07V-R	
		min.	1.5 Nm	
		max.	4 Nm	
		nominal	4 Nm	
	wire end ferrule	Stripping length	min.	8 mm
			max.	8 mm
			nominal	8 mm
		Tightening torque	min.	0.4 inch
			max.	0.4 inch
		Recommended wire-end ferrule		
	Connection specification		Screw connection	
	Cross-section for conductor connection	Type	flexible, H05(07) V-K	
		min.	0.5 Nm	
		max.	4 Nm	
nominal		4 Nm		
wire end ferrule	Stripping length	min.	8 mm	
		max.	8 mm	
		nominal	8 mm	
	Tightening torque	min.	0.4 inch	
		max.	0.4 inch	
	Recommended wire-end ferrule			
Clamping range, max.		4 Nm		
Clamping range, min.		0.5 Nm		
Clamping screw		M 3		
Connection cross-section, stranded, max.		4 Nm		
Connection cross-section, stranded, min.		1.5 Nm		
Connection direction		on side		
Gauge to IEC 60947-1		A3		
Number of connections		2		
Stripping length		8 mm		
Tightening torque, max.		0.4 inch		
Tightening torque, min.		0.4 inch		
Torque level with DMS electric screwdriver		2		
Type of connection		Screw connection		
Wire connection cross section AWG, max.		AWG 12		
Wire connection cross section AWG, min.		AWG 22		
Wire connection cross section, finely stranded, max.		4 Nm		

WSI 4

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max. 2.5 Nm

Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min. 0.5 Nm

Wire connection cross-section, solid core, max. 4 Nm

Wire connection cross-section, solid core, min. 0.5 Nm

Dimensions

TS 35 offset 32.5 mm

Display element

Operating voltage for display, max. 500 V

Fuse terminals

Cartridge fuse G-Si. 5 x 20

Fuse holder (cartridge holder) Pivoting

Power loss for overload and short-circuit protection for a composite arrangement 1.6 W at 6.3 A @ 23°C

Power loss for short-circuit protection only for a composite arrangement 2.5 W at 6.3 A @ 47°C

Display Without LED

Operating voltage, max. 250 V

Power loss for overload and short-circuit protection for an individual arrangement 1.6 W at 6.3 A @ 34°C

Power loss for short-circuit protection only for an individual arrangement 4.0 W at 6.3 A @ 63°C

General

Rail TS 35

Wire connection cross section AWG, max. AWG 12

Standards IEC 60947-7-3

Wire connection cross section AWG, min. AWG 22

Rating data

Rated cross-section 4 Nm

Rated voltage to adjoining terminal 500 V

Current at maximum wires 6.3 A

Volume resistance according to IEC 60947-7-x 1 °C

Power loss in accordance with IEC 60947-7-x 1.02 W

Rated voltage 250 V

Rated current 6.3 A

Standards IEC 60947-7-3

Rated impulse withstand voltage 6 kV

Pollution severity 3

UL rating data

Certificate No. (cURus) E60693

Conductor size Factory wiring min. (cURus) 30 AWG

Conductor size Field wiring min. (cURus) 30 AWG

Current size C (cURus) 15 A

UL_voltage_Print 300 V

UL_wire_min_Print 30 A / 6 A / 10 A / 13 A / 15 A

Voltage size C (cURus) 300 V

Conductor size Factory wiring max. (cURus) 12 AWG

Conductor size Field wiring max. (cURus) 12 AWG

Current size B (cURus) 15 A

UL_current_Print 15 A

UL_wire_max_Print 12 A / 6 A / 10 A / 13 A / 15 A

Voltage size B (cURus) 300 V

WSI 4

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Classifications

ETIM 6.0	EC000899	ETIM 7.0	EC000899
ETIM 8.0	EC000899	ECLASS 9.0	27-14-11-16
ECLASS 9.1	27-14-11-16	ECLASS 10.0	27-14-11-16
ECLASS 11.0	27-14-11-16		

Approvals

Approvals



ROHS	Conform
UL File Number Search	E60693

Downloads

Approval/Certificate/Document of Conformity	CB Testreport CB Certificate CB Test certificate EAC certificate Lloyds Register Certificate Declaration of Conformity Declaration of Conformity all terminals
Engineering Data	STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S
User Documentation	StorageConditionsTerminalBlocks
Catalogues	Catalogues in PDF-format
Brochures	

WSI 4

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

