

LSP 4L**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

The main function of the voltage tester is to establish if voltage is present. A 2-pole voltage tester is the only approved testing instrument that fulfils the requirements of work protection regulations.

- with LCD-Display
- acc. to VDE standard,
- high peak voltage strength
- the right tester for every application

General ordering data

Version	Testing tools, 2-pole voltage tester type 1153
Order No.	9205050000
Type	LSP 4L
GTIN (EAN)	4032248697311
Qty.	1 pc(s).

LSP 4L

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	48 mm	Depth (inches)	1.89 °C
Height	37 mm	Height (inches)	1.457 °C
Width	231 mm	Width (inches)	9.094 °C
Weight	170 g	Net weight	173.5 g

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Technical data

Description of article	Two-pole voltage and continuity tester for up to 690 V
------------------------	--

Measuring and testing devices

AC voltage measuring range	12-690 V	Continuity test	Yes
DC voltage measuring range	690 V	Display	digital
Frequency range, max.	500 Hz	Frequency range, min.	0 Hz
Measuring range category	CAT III – 690V/CAT IV – 600V	Peak voltage resistance	8 kV
Protection degree	IP65	Rated voltage, max.	690 V AC/DC
Rated voltage, min.		Tested and approved according to	EN/IEC 61243-3 :2010-10 (VDE 0682 Part 401)
	12 V AC/DC	Working temperature, min.	-15 °C
Working temperature, max.	45 °C		

Classifications

ETIM 6.0	EC000494	ETIM 7.0	EC000494
ETIM 8.0	EC000494	ECLASS 9.0	27-20-03-08
ECLASS 9.1	27-20-03-08	ECLASS 10.0	27-20-03-08
ECLASS 11.0	27-20-03-08		

Approvals

Approvals



ROHS

Conform

Downloads

Approval/Certificate/Document of Conformity	9205050000_DECLARATION_OF_CONFORMITY.pdf
User Documentation	Manual
Catalogues	Catalogues in PDF-format
Brochures	