

**BEST****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image**

The component plug is used to integrate an electrical component in a disconnect terminal block. After soldering the electronic component, the plug can be integrated into the disconnection area of our disconnect terminal blocks and thus changes the disconnect terminal block into a modular terminal block with integrated electronic component.

**General ordering data**

| Accessories, Component plug |                            |
|-----------------------------|----------------------------|
| Version                     |                            |
| Order No.                   | <a href="#">1833100000</a> |
| Type                        | BEST                       |
| GTIN (EAN)                  | 4032248501014              |
| Qty.                        | 50 pc(s).                  |

**BEST****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |         |                 |          |
|------------|---------|-----------------|----------|
| Depth      | 63 mm   | Depth (inches)  | 2.48 °C  |
| Height     | 49.5 mm | Height (inches) | 1.949 °C |
| Width      | 5 mm    | Width (inches)  | 0.197 °C |
| Net weight | 3.72 g  |                 |          |

**Material data**

|          |       |        |       |
|----------|-------|--------|-------|
| Material | Wemid | Colour | beige |
|----------|-------|--------|-------|

**System specifications**

|         |      |
|---------|------|
| Version | Plug |
|---------|------|

**Additional technical data**

|                          |         |                     |                 |
|--------------------------|---------|---------------------|-----------------|
| Explosion-tested version | No      | Installation advice | Direct mounting |
| Type of fixing           | Plugged | Type of mounting    | Plugged         |

**Conductors for clamping (rated connection)**

|                    |               |
|--------------------|---------------|
| Type of connection | Miscellaneous |
|--------------------|---------------|

**Dimensions**

|                 |        |
|-----------------|--------|
| Pitch in mm (P) | 5.1 mm |
|-----------------|--------|

**General**

|                     |                 |
|---------------------|-----------------|
| Installation advice | Direct mounting |
|---------------------|-----------------|

**Rating data**

|               |       |
|---------------|-------|
| Rated voltage | 250 V |
|---------------|-------|

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002018    | ETIM 7.0    | EC002018    |
| ETIM 8.0    | EC002018    | ECLASS 9.0  | 27-14-11-49 |
| ECLASS 9.1  | 27-14-11-49 | ECLASS 10.0 | 27-14-11-49 |
| ECLASS 11.0 | 27-14-11-49 |             |             |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                             |                                                            |
|-----------------------------|------------------------------------------------------------|
| Engineering Data            | <a href="#">36278_BEST_DXF.dxf</a><br><a href="#">STEP</a> |
| Engineering Data            | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                   |
| Product Change Notification | <a href="#">PCN - EN</a><br><a href="#">PCN - DE</a>       |
| User Documentation          | <a href="#">StorageConditionsTerminalBlocks</a>            |
| Catalogues                  | <a href="#">Catalogues in PDF-format</a>                   |
| Brochures                   |                                                            |

Creation date July 23, 2021 3:07:17 PM CEST