

WDU 240**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image****Power feed-in**

Our wide range of W-Series terminal blocks with our WPD main line branch terminals, which are optimised to guarantee both convenience and space gains, ensures a secure and convenient connection at the power feed-in.

General ordering data

Version	Feed-through terminal, Screw connection, 240 mm ² , 1000 V, 415 A, dark beige
Order No.	1802780000
Type	WDU 240
GTIN (EAN)	4032248313723
Qty.	2 pc(s).

WDU 240

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	123.7 mm	Depth (inches)	4.87 °C
Depth including DIN rail	124 mm	Height	100 mm
Height (inches)	3.937 °C	Width	36 mm
Width (inches)	1.417 °C	Net weight	472.5 g

Temperatures

Storage temperature		Operating temperature range	For operating temperature range see EC Design Test Certificate / IEC Ex-Certificate of Conformity
	-25 °C...55 °C		
Continuous operating temp., min.	-60 °C	Continuous operating temp., max.	120 °C

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Material data

Material	Wemid	Colour	dark beige
UL 94 flammability rating	V-0		

Rating data IECEx/ATEX

Certificate No. (ATEX)	KEMA01ATEX2186U	Max. voltage (ATEX)	1100 V
Current (ATEX)	350 A	Wire cross section max. (ATEX)	240 mm²
Operating temperature range	For operating temperature range see EC Design Test Certificate / IEC Ex-Certificate of Conformity	Marking EN 60079-7	
			Ex eb II C Gb
Ex 2014/34/EU label	II 2 G D		

System specifications

Version	Screw connection, for screwable cross-connection, in closed state	End cover plate required	No
Number of potentials	1	Number of levels	1
Number of clamping points per level	2	Number of potentials per tier	1
Levels cross-connected internally	No	PE connection	No
Rail	TS 32, TS 35	N-function	No
PE function	No	PEN function	Yes

2 clampable conductors (H05V/H07V) with equal cross-section (rated connection)

Cross-section for connected wire, stranded, two clampable wires, max.	95 Nm	Cross-section for connected wire, stranded, two clampable wires, min.	35 Nm
Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, 2 clampable wires, max.	50 Nm	Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, 2 clampable wires, min.	35 Nm
Wire connection cross section, finely stranded, two clampable wires, min.	50 Nm	Wire cross-section, finely stranded, two clampable wires, max.	95 Nm

WDU 240

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Additional technical data

Explosion-tested version	Yes	Number of similar terminals	1
Open sides	closed	Type of mounting	Snap-on

CSA rating data

Certificate No. (CSA)	213329	Current size C (CSA)	400 A
Voltage size C (CSA)	600 V	Wire cross section max. (CSA)	500 kcmil
Wire cross section min. (CSA)	0 AWG		

Conductors for clamping (rated connection)

Blade size	S8 (DIN 6911)				
Clampable conductor	Connection specification		Screw connection		
	Cross-section for conductor connection	Type	stranded, H07V-R		
		min.	70 Nm		
		max.	240 Nm		
		nominal	240 Nm		
	wire end ferrule	Stripping length	min.	40 mm	
			max.	40 mm	
			nominal	40 mm	
		Tightening torque	min.	25 inch	
			max.	30 inch	
		Recommended wire-end ferrule			
	Connection specification		Screw connection		
	Cross-section for conductor connection	Type	flexible, H05(07) V-K		
		min.	70 Nm		
		max.	240 Nm		
		nominal	240 Nm		
	wire end ferrule	Stripping length	min.	40 mm	
			max.	40 mm	
			nominal	40 mm	
		Tightening torque	min.	25 inch	
			max.	30 inch	
		Recommended wire-end ferrule			
Clamping range, max.	240 Nm				
Clamping range, min.	70 Nm				
Clamping screw	M 10				
Connection cross-section, stranded, max.	240 Nm				
Connection cross-section, stranded, min.	70 Nm				
Connection direction	on side				
Gauge to IEC 60947-1	B15				
Number of connections	2				
Stripping length	40 mm				
Tightening torque, max.	30 inch				
Tightening torque, min.	25 inch				
Type of connection	Screw connection				
Wire connection cross section, finely stranded, max.	240 Nm				
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max.	185 Nm				

WDU 240

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min. 70 Nm

Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max. 185 Nm

Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min. 70 Nm

General

Rail	TS 32, TS 35	Standards	IEC 60947-7-1
------	--------------	-----------	---------------

Rating data

Rated cross-section	240 Nm	Rated voltage	1,000 V
Rated DC voltage	1,000 mm ²	Rated current	415 A
Current at maximum wires	415 A	Standards	IEC 60947-7-1
Volume resistance according to IEC 60947-7-x	0.08 °C	Rated impulse withstand voltage	8 kV
Power loss in accordance with IEC 60947-7-x	13.28 W	Pollution severity	3

UL rating data

Certificate No. (UR)	E175455	Current size C (UR)	380 A
UL_current_Print	380 A	UL_voltage_Print	600 V
UL_wire_max_Print	500 MBit/s	Voltage size C (UR)	600 V
Wire cross section max. (UR)	500 kcmil		

Classifications

ETIM 6.0	EC000897	ETIM 7.0	EC000897
ETIM 8.0	EC000897	ECLASS 9.0	27-14-11-20
ECLASS 9.1	27-14-11-20	ECLASS 10.0	27-14-11-20
ECLASS 11.0	27-14-11-20		

Approvals

Approvals



ROHS	Conform
UL File Number Search	E175455

WDU 240

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Downloads

Approval/Certificate/Document of Conformity	Attestation of Conformity
	CB Testreport
	CB Certificate
	ATEX Certificate
	EAC certificate
	INMETRO certificate
	EAC EX Certificate
	Declaration of Conformity
	Declaration of Conformity all terminals
Engineering Data	STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S
User Documentation	Cross Connection Guide
	StorageConditionsTerminalBlocks
Catalogues	Catalogues in PDF-format
Brochures	

WDU 240

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings

