

TS 32X15 2M/ST/ZN**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Product image**

Steel DIN rails are the most widespread on the market. Among metal DIN rails, they have the lowest shortcircuit protection, similar to stainless steel.

General ordering data

Version	Rail, TS 32, without slot, Steel, galvanic zinc plated and passivated
Order No.	0122800000
Type	TS 32X15 2M/ST/ZN
GTIN (EAN)	4008190066307
Qty.	2 m

TS 32X15 2M/ST/ZN

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	15 mm	Depth (inches)	0.591 °C
Height	33 mm	Height (inches)	1.299 °C
Width	2,000 mm	Width (inches)	78.74 °C
Net weight	720 g		

Mounting rail

Installation advice	Direct mounting	
Length of the terminal rail	min.	0 mm
	max.	2,000 mm
	nominal	2,000 mm
Material	Steel	
Pre-punched mounting rail	No	
Short circuit strength corresponds to E-Cu wire	35 Nm	
Short-time withstand current according to IEC 60947-7-2	4.2 V AC/DC ±10 %	
Slit gap		
Slit length		
Slit width		
Standards	DIN EN 60715	
Surface finish	galvanic zinc plated and passivated	
Thickness	1.5 mm	

Classifications

ETIM 6.0	EC001285	ETIM 7.0	EC001285
ETIM 8.0	EC001285	ECLASS 9.0	27-40-06-02
ECLASS 9.1	27-40-06-02	ECLASS 10.0	27-40-06-02
ECLASS 11.0	27-40-06-02		

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD, Zuken E3.S
User Documentation	StorageConditionsTerminalBlocks
Catalogues	Catalogues in PDF-format
Brochures	